

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-2386-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brinninstool

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 20, T-23S,

R-33E

12. COUNTY OR PARISH

Lea

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

American Quasar Petroleum Co. of New Mexico

3. ADDRESS OF OPERATOR

606 Vaughn Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1980' FN&EL, Section 20, T-23S, R33E

U. S. GEOLOGICAL SURVEY

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, or GR)

3688 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Setting casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1-7-75: 700' - 20" casing - 900 sx cement - cement circulated  
1-25-75: 5120' - 13 3/8" casing - 3600 sx cement - Top of cement @ 710'.  
3-11-75: 12560' - 9 5/8" casing - First stage: 2600 sx - circulated  
100 sx through DV tool @ 4980'.  
Second stage: 1150 sx. Top of cement @ 1140'.

5-17-75: 15950' - 5" Liner back to 12,248' - Cemented with 1175 sx.

18. I hereby certify that the foregoing is true and correct.

SIGNED

Jack Patchell

TITLE Operations Engineer

DATE 5-27-75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD  
MAY 28 1975

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side