

Submit 3 Copies
to Appropriate
District Office

DISTRICT I

P.O. Box 1980, Hobbs, NM 88241-1980

DISTRICT II

811 S. First Street, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, New Mexico 87505

WELL API NO.

30-025-24916

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

K-2149

7. Lease Name or Unit Agreement Name

Antelope Ridge Unit

8. Well No.

#5

9. Pool Name or Wildcat

96100 SWD; Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL

GAS

WELL ☐

WELL ☐

OTHER

SWD

2. Name of Operator

021712 STRATA PRODUCTION COMPANY

3. Address of Operator

P.O. BOX 1030, ROSWELL, NEW MEXICO 88202-1030

4. Well Location

Unit Letter L : 2310 Feet From The South Line and 990 Feet From The West Line

Section 33 Township 23 South Range 34 East NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3540' DF

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

AMEND C-103 DATED 11/14/95

OTHER: TO CONVERT TO SWD ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)
SEE RULE 1103

09/08/95: MIRU. NU BOP.

09/09/95: Drill out surface plug to 120'. Test casing to 800#. Held OK. Drill out plug from 1169' to 1298'.
Test casing to 750#. Held OK. Circulate hole clean.

09/11/95: Drill out plugs at 5190' and 5259' to 5386'. Drill 8 5/8" hole to 6778'. Circulate hole clean.

09/12/95: Cement at 6778' with 338 sacks 50/50 Poz 'C' with additives. Reverse out 1 barrel cement. WOC.

09/13/95: Tag TOC at 6134'. PBTD 6134'. TIH with tubing. ND BOP. NU wellhead.

09/18/95: Acidize open-hole at 5167' to 6134' with 3000 gallons 7 1/2% NEFE. Flow back.

10/27/95: TIH with ceramic coated 2 7/8" tubing and 10 3/4" plastic coated Loc-Set packer. Set packer at 5118'.
Pressure test to 500# for 30 minutes. Held OK. Chart attached.

11/01/95: Set pump and suction, discharge and flow lines. Start filling battery.

11/05/95: Start injection.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Carol J. Garcia TITLE PRODUCTION RECORDS MANAGER DATE 7/3/96

TYPE OR PRINT NAME CAROL J. GARCIA TELEPHONE NO. 505-622-1127

(This space for State Use)

APPROVED BY CAROL J. GARCIA TITLE PRODUCTION RECORDS MANAGER DATE JUL 24 1996
CONDITIONS OF APPROVAL, IF ANY: