

|                        |  |
|------------------------|--|
| NO. OF COPIES RECEIVED |  |
| DISTRIBUTION           |  |
| DATE                   |  |
| FILE                   |  |
| U.S.G.S.               |  |
| LAND OFFICE            |  |
| OPERATOR               |  |

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101  
Revised 1-1-65 *30 CP-2512*

|  |  |  |  |
|--|--|--|--|
| <b>APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK</b>   |  |  |  |
| 1a. Type of Work<br>DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/>   |  | 5A. Indicate Type of Lease<br>STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |  |
| b. Type of Well<br>OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> SINGLE ZONE <input type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/> |  | 5. State Oil & Gas Lease No.   |  |
| 2. Name of Operator<br>Gulf Oil Corporation  |  | 7. Unit Agreement Name   |  |
| 3. Address of Operator<br>Box 670, Hobbs, New Mexico 88240   |  | 8. Firm or Lease Name<br>H. T. Mattern (NCT-D)   |  |
| 4. Location of Well<br>UNIT LETTER <u>F</u> LOCATED <u>1980</u> FEET FROM THE <u>North</u> LINE<br>AND <u>1650</u> FEET FROM THE <u>WEST</u> LINE OF SEC. <u>6</u> TWP. <u>22-S</u> RGE. <u>37-E</u> NMPM    |  | 9. Well No.<br><u>11</u>   |  |
|  |  | 10. Field and Pool, or Wildcat<br>Drinkard   |  |
|  |  | 12. County<br>Lea  |  |
|  |  | 19. Proposed Depth<br><u>6800'</u>   |  |
|  |  | 19A. Formation<br>Drinkard   |  |
|  |  | 20. Rotary or C.T.<br>Rotary   |  |
| 21. Elevations (Show whether DE, RT, etc.)<br><u>3457' GL</u>  |  | 21A. Kind & Status Plug. Bond<br>Blanket   |  |
|  |  | 21B. Drilling Contractor   |  |
|  |  | 22. Approx. Date Work will start<br><u>April 15, 1975</u>  |  |

23. PROPOSED CASING AND CEMENT PROGRAM

| SIZE OF HOLE | SIZE OF CASING | WEIGHT PER FOOT | SETTING DEPTH | SACKS OF CEMENT | EST. TOP |
|--------------|----------------|-----------------|---------------|-----------------|----------|
| 11"          | 8-5/8"         | 24#             | 1150'         | Circulate       |          |
| 7-7/8"       | 5-1/2"         | 14#             | 6800'         | Base of Salt    |          |

BOP: See Drawing No. 3 attached.

APPROVAL VALID  
FOR 90 DAYS UNLESS  
DRILLING COMMENCED,  
EXPIRES 7-4-75

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM; IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed *[Signature]* Title Area Engineer Date April 3, 1975

(This space for State Use)

APPROVED BY *[Signature]* TITLE SUPERVISOR DISTRICT I DATE APR 1975

CONDITIONS OF APPROVAL, IF ANY:

NEW MEXICO OIL CONSERVATION COMMISSION  
WELL LOCATION AND ACREAGE DEDICATION

Form O-101  
Superseded O-128  
Effective 1-1-65

All distances must be from the outer boundaries of the Section


|                      |  |                              |  |                    |  |                         |  |          |  |
|----------------------|--|------------------------------|--|--------------------|--|-------------------------|--|----------|--|
| Gulf Oil Corporation |  | Lease                        |  | H.T. Mattern NCT-D |  | Well No.                |  | 11       |  |
| Section              |  | Township                     |  | Range              |  | County                  |  |          |  |
| 6                    |  | 22 South                     |  | 37 East            |  | Lea                     |  |          |  |
| 1920                 |  | feet from the North line and |  | 1650               |  | feet from the West line |  |          |  |
| 2456.6               |  | Drinkard                     |  | Drinkard           |  | Dedicated Acreage       |  | 40 Acres |  |

- Outline the acreage dedicated to the subject well by colored pencil or hatchure marks on the plat below.
- If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
- If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

Yes ☐ No ☐ If answer is "yes," type of consolidation \_\_\_\_\_

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) \_\_\_\_\_

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.



CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

*B. J. Pankratz*

Name

B. J. PANKRATZ

Position

Area Engineer

Company

Gulf Oil Corporation

Date

April 3, 1975

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed


April 1, 1975


Registered Professional Engineer and/or Land Surveyor

*John W. West*

Certificate No.

676





### 3000 PSI WORKING PRESSURE BLOWOUT PREVENTER HOOK-UP

The blowout preventer assembly shall consist of one blind ram preventer and one pipe ram preventer, both hydraulically operated; a Hydril "GK" preventer, valves, chokes and connections as illustrated. If a tapered drill string is used, a ram preventer must be provided for each size of drill pipe. Casing and tubing rams to fit the preventers are to be available as needed. If correct in size, the flanged outlets of the ram preventer may be used for connecting to the 4-inch I.D. choke flow line and kill line, except when air or gas drilling. The substructure height shall be sufficient to install a rotating blowout preventer.

Minimum operating equipment for the preventers and hydraulically operated valves shall be as follows: (1) Multiple pumps, driven by a continuous source of power, capable of fluid changing the total accumulator volume from the nitrogen precharge pressure to its rated pressure within \_\_\_\_\_ minutes. Also, the pumps are to be connected to the hydraulic operating system which is to be a closed system. (2) Accumulators with a precharge of nitrogen of not less than 750 PSI and connected so as to receive the aforementioned fluid change. With the changing pumps shut down, the pressurized fluid volume stored in the accumulators must be sufficient to close all the pressure-operated devices simultaneously within \_\_\_\_\_ seconds; after closure, the remaining accumulator pressure shall be not less than 1000 PSI with the remaining accumulator fluid volume of at least \_\_\_\_\_ percent of the original. (3) When required, an additional source of power, remote and equivalent, is to be available to operate the above pumps; or there shall be additional pumps operated by separate power and equal in performance capabilities.

The closing manifold and remote closing manifold shall have a separate control for each pressure-operated device. Controls are to be labeled, with control handles indicating open and closed positions. A pressure reducer and regulator must be provided for operating the Hydril preventer. When requested, a second pressure reducer shall be available to limit operating fluid pressures to ram preventers. Gulf Legion No. 38 hydraulic oil, an equivalent or better, is to be used as the fluid to operate the hydraulic equipment.

The choke manifold, choke flow line, and choke lines are to be supported by metal stands and adequately anchored. The choke flow line and choke lines shall be constructed as straight as possible and without sharp bends. Easy and safe access is to be maintained to the choke manifold. All valves are to be selected for operation in the presence of oil, gas, and drilling fluids. The choke flow line valves connected to the drilling spool and all ram type preventers must be equipped with stem extensions, universal joints if needed, and hand wheels which are to extend beyond the edge of the derrick substructure. All other valves are to be equipped with handles.

\* To include derrick floor mounted controls.

173

RECEIVED

LIBRARY  
UNIVERSITY OF CALIFORNIA  
LIBRARY