

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
HOBBS, NEW MEXICO 88240

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 18307

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Monsanto Oil Company

3. ADDRESS OF OPERATOR

1300 One First City Center, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

990 FNL & 1980 FEL

7. UNIT AGREEMENT NAME

Antebellum Unit

8. FARM OR LEASE NAME

Antebellum Unit

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Bell Lake Bone Springs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 29, T-23-S, R-34-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GL 3514, KB 3533

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☒

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/2/83 - Pulled tubing out Model D packer.

8/3/83 - RU and ran junk basket & gauge ring, ran 7" 35# CIBP set @ 12,150'.

8/4/83 - Ran CR CCL log 8900'-6900', Ran in hole w/tubing to 12125', displaced hole w/1300 Bbls. 9.5# brine water.

8/5/83 - Set 25 sxs cement plug @ 12,125', set 50 sxs plug @ 10,500', set 50 sxs plug @ 9107' Spot 400 gals 10% Acetic acid.

8/9/83 - Perf Bone Springs w/1 shot per foot 8803'-8672', 20 holes.

8/11/83 - RIH w/packer & tubing, A/7500 gals 15% acid.

8/16/83 - Recovered all acid water, well not productive and shut in. Wait on P & A.



18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE Regional Prod. Mgr.

DATE 9/26/83

(This space for Federal or State office use)

ACCEPTED FOR RECORD

DATE

[Signature]

SEP 27 1983

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO

RECEIVED

SEP 29 1983

O.C.D.
HOBBS OFFICE

O.C.D.
HOBBS OFFICE