

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease	
STATE ☐	FEE ☒
5. State Oil & Gas Lease No.	

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		7. Unit Agreement Name	
b. Type of Well OIL WELL ☒ GAS WELL ☐ OTHER ☐		8. Farm or Lease Name Hugh	
2. Name of Operator Gulf Oil Corporation		9. Well No. 11	
3. Address of Operator Box 670, Hobbs, New Mexico 88240		10. Field and Pool, or Wildcat Wantz Granite Wash	
4. Location of Well UNIT LETTER B LOCATED 410 FEET FROM THE North LINE AND 1960 FEET FROM THE East LINE OF SEC. 14 TWP. 22-S RGE. 37-E NMPM		12. County Lea	
19. Proposed Depth 7450'		19A. Formation Granite Wash	
20. Rotary or C.T. Rotary		21. Elevation (Show whether DF, RT, etc.) 3339' GL	
21A. Kind & Status Plug. Bond Blanket		21B. Drilling Contractor	
22. Approx. Date Work will start July 20, 1975			

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
11"	8-5/8"	24#	1150	Circulate	
7-7/8"	5-1/2"	15.50#	7450'	Base of Salt	

BOP: See Drawing No. 3 attached.

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED,

EXPIRES

10/14/75

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE, GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.


I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed _____ Title Area Production Manager Date July 11, 1975


(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:



See Detail of 4" Flow
Line and Choke Assembly



3,000 PSI WORKING PRESSURE
KILL, CHOKE, AND FILL CONNECTIONS

API Series 900 Flanges or Bells

DETAIL OF 4" FLOW LINE CHOKE ASSEMBLY

Minimum assembly for 3000 PSI working pressure will consist of three preventers. The bottom end middle preventers may be Cameron ORC, Cameron Type F single or Sheffield Hydraulic single, and the upper will be Hydril GK. In lieu of the center spool, the flanged outlets from the Cameron Type F single open face flanged preventer, provided the outlets are the correct size, may be used for the four-inch flow line and the two-inch kill line.

Size 12-inch preventers may be used for work down through 9- $\frac{5}{8}$ -inch casing. Size 10-inch preventers may be used for work down through 7- $\frac{3}{4}$ -inch casing. Size six-inch preventers are to be used for work through 7-inch and 5- $\frac{1}{2}$ -inch casings.

Minimum operating equipment for the preventers will be: (1) An air operated pump and (2) An accumulator(s) with some means of obtaining a fluid charge. A closed fluid system is recommended. The closing manifold and remote closing manifold will have a separate four-way valve for each pressure operated device and a Hydril regulator will be provided. Sufficient fluid capacity in the accumulator(s) shall be available to close off the pressure operated devices of the same time within 25 percent reserve. Gulf No. 561 hydraulic oil shall be used as the operating fluid.

The four-inch flow line from the preventers shall be supported by a metal stand or reinforced concrete. All valves throughout the assembly shall be selected for operation in both gas and fluids.

The ram type preventers and the Cameron HCR valve will be provided with stem extensions, if needed, and operating wires.

3,000 PSI WORKING PRESSURE
ELBOWOUT PREVENTER HOOK-UP

Series 300 Flanges, & Bellows