

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPM OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Gulf Oil Corporation 3. Address of Operator Box 670, Hobbs, New Mexico 88240 4. Location of Well UNIT LETTER E 1650 FEET FROM THE North LINE AND 610 FEET FROM THE West LINE, SECTION 7 TOWNSHIP 22-S RANGE 37-E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3455' GL	7. Unit Agreement Name 8. Farm or Lease Name H. T. Mattern (NCT-D) 9. Well No. 16 10. Field and Pool, or Wildcat Undes. Drinkard 12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Capitan Drilling Company spudded 11" hole at 12:00 Noon, August 28, 1975. Drilled to 1085'. Ran 28 joints, 1068' of 8-5/8" OD 24# K-55 ST&C casing set and cemented at 1082' with 300 sacks of Class C cement containing 4% gel and 2% Ca C12 and 200 sacks of Class C containing 2% Ca C12. Cement circulated. WOC & NU 22 hours. Tested casing with 1200#, 30 minutes, OK.

Started drilling 7-7/8" hole at 1085' at 10:45 AM, August 30, 1975.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>D. F. Berlin</u>	TITLE <u>Area Engineer</u>	DATE <u>September 4, 1975</u>
Orig. Signed by <u>John Runyan</u> Geologist	TITLE <u></u>	DATE <u></u>
APPROVED BY <u></u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		