

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator GULF OIL CORPORATION	8. Farm or Lease Name H. T. Mattern (NCT-D)
3. Address of Operator P. O. Box 670, Hobbs, NM 88240	9. Well No. 17
4. Location of Well UNIT LETTER F 1650 FEET FROM THE North LINE AND 1720 FEET FROM THE West LINE, SECTION 7 TOWNSHIP 22S RANGE 37E NMPM.	10. Field and Pool, or Wildcat Tubb
15. Elevation (Show whether DF, RT, GR, etc.) 3450' GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER Downhole commingle Tubb & Drinkard <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Kill well if necessary w/8.6# GKF. POH w/rods, pump & 2-3/8" tbg. GIH w/bit & DC's on tubing. Drl up CIBP @ 6390'. Clean out to 6698'. Re-run 2-3/8" tbg plus additional 2-3/8" tbg as needed. Run pump & rods plus additional rods as needed (API specs are (34%) 7/8" rods & (66%) 3/4" rods). Hang well on.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED N. G. Sklar Jr. TITLE Area Engineer DATE 4-14-80

APPROVED BY Jerry Sexton TITLE Dist. L. Supv. DATE 4-15-80

CONDITIONS OF APPROVAL, IF ANY: