OPERATOR'S COPY

Form 9-331 Dec. 1973

Form Approved.

Budget Bureau No. 42-R1424

UNITED STATES

UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
	8. FARM OR LEASE NAME Elliott B-13
1. oil gas cother start well other	9. WELL NO.
2. NAME OF OPERATOR	2
Sun Exploration & Production Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Drinkard/Wantz Granit Wash
P.O. Box 1861, Midland, TX 79702	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) Unit Ltr. "E" AT SURFACE:	Sec. 13. T-22-S, R-37-E 12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: 510' FWL & 2100' FNL	Lea New Mexico
AT TOTAL DEPTH:	14. API NO
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3333' GL 3343' DF
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	(NOTE: Depart results of multiple and law
PULL OR ALTER CASING T	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	119 000
ARANDON*	
(other) Add perfs (Granite Wash) & Frac	
Acd Drivkered	· ·
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine	directionally drilled, give subsurface locations and
01/20 MIRU DA & S W.S. Hot OIL CSG w145 BBLS.	LSE OIL, POH W/ Short string
rods left 5 rods & pump in (drinkard) 2-	-3/8 TBG. ୍ରସ୍ଥିତ କୁ ଲୁଟ୍ରିମ
01/21 R/H w/ Parafin scraper, CLN out parafin	2500 - SURF. RIH w/2" fishing
tool w/ 1-5/8 grapple, latch rods, POH w	//fishing tool, rec. all rods
& pump, SD due to bad weather.	그리는 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
01/22 Release parallel string Anchor, POH w/2-	3/8 uppor TRG Pleased otis 7"
01/22 Release parallel string Anchor, POH w/2- perma latch PKR. POH w/PKR & 2-3/8 TBG t	10 2480'
perma fatch rkk. Foll wyrkk a 2 3/0 ida t	
01/23 Finis POH w/OTIS Pkr & 2-3/8 (LS) TBG.	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED DEETMN TITLE Accounting	affst DATE 6-9-83
COEPTED FOR SECURITY Space for Federal or State of	
APPROVED BY APPROVAL HE ANY	DATE
conditions of APPROVAL FF ANY: 6 1983	1997年 - 1997年 - 李素秀華 - 1997年 -

MODELS OFFICE