

11) FRAC AS FOLLOWS: MAX PRESSURE 4500 PSI. RATE 10-12 BPM.

- A) Pump 2000 GALLONS LEASE CRUDE PRE-PAD
- B) Pump 2000 GALLONS MY-T-OIL II PAD
- C) Pump 2000 GALLONS MY-T-OIL II w/1 lb/GAL 10/20 SAND
- D) Pump 2000 GALLONS MY-T-OIL II w/2 lb/GAL 10/20 SAND
- E) Pump 2000 GALLONS MY-T-OIL II w/2 1/2 lb/GAL 10/20 SAND
- F) Pump 2000 GALLONS MY-T-OIL II w/3 lb/GAL 10/20 SAND
- G) FLUSH TO PERFS w/LEASE CRUDE. Do NOT OVERFLUSH.
- H) Shut-in OVERNIGHT TO LET GEL BREAK (4-6 Hour Break GEL)

12) RUN TUBING WITH SEATING NIPPLE & MUD ANCHOR.
Pump TEST.

NOTE: LEASE OIL - OBTAIN FROM ANOTHER RAMSEY SAND
PRODUCING LEASE. EXAMPLES MARSHALL-FIELD-N. ELMAR.
GEL SAMPLE OF EACH LEASE CRUDE TO OBSERVE
GELLING PROPERTIES BEFORE FRAC.

RAF

10-24-78

2

2

RECOMPLETE IN RAMSEY SAND.