

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. LC-032104	
2. NAME OF OPERATOR TEXACO Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -	
3. ADDRESS OF OPERATOR P.O. Box 728 Hobbs, New Mexico 88240		7. UNIT AGREEMENT NAME -	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Well is located 660' FSL & 660' FEL of Section 19, T-22-S, R-38-E, Unit Letter P, Lea County, New Mexico.		8. FARM OR LEASE NAME A.H. Blinebry Fed NCT-1	
14. PERMIT NO. Regular		9. WELL NO. 40	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3374' (GR)		10. FIELD AND POOL, OR WILDCAT Drinkard	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 19. T-22-S, R-38-E	
		12. COUNTY OR PARISH Lea	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Open Drinkard Zone ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up. Pull rods and pump. Install BOP. Pull tubing.
2. Set CIBP @ 7320'. Temporarily abandon Granite Wash, 7-23-77.
3. Perforate 7" csg liner in Drinkard Zone w/1-JSPF @ 6955', 65', 78', 82', 7010', 22', 67', 78', 97', 7111', 21', 32', 54', 68', 81', 7206', 11', 17', & 7234'.
4. Set pkr. @ 6860'. Acidize 7" csg perforations 6955'-7234' w/3200 gal 15% NE Acid using 30 Ball Sealers. Flush w/55 gal treated water.
5. Set RBP @ 6865' and dump 2 sx sand on top of plug.
6. Perforate 7" csg liner in Drinkard Zone w/1-JSPF @ 6366', 6403', 19', 41', 65', 66', 96', 6678', 87', 91', 6701', 16', 23', 33', 39', 61', 75', 80', 86', & 6793'.
7. Set pkr @ 6298'. Acidize 7" csg liner perfs 6366'-6793' w/4100 gal 15% NE Acid w/30 ball sealers. Flushed w/55 bbls treated water. Pull RBP.
8. Install pumping equipment. On 24 hr potential test, well pumped 11 BO and 4 BW, GOR 2000. Job complete 11:00 AM 8-10-77.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Asst. Dist. Supt.

DATE 8-11-77

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD	
DATE 8-15-1977	
J. S. GEOLOGICAL SURVEY	
HOBBS, NEW MEXICO	

*See Instructions on Reverse Side

RECEIVED

APR 1 1977

OIL CO. OF NEW MEXICO
HOBBS, N. M.