

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-025-25211

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement
Name:

BLINEBRY-DRINKARD

8. Well No.

A-22

9. Pool name or Wildcat
SAN ANDRES

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other SWD Well

2. Name of Operator

RICE OPERATING COMPANY

3. Address of Operator

122 W. TAYLOR, HOBBS, NM 88240

4. Well Location

Unit Letter A : 817 feet from the NORTH line and 965 feet from the EAST line

Section 22

Township 22S Range 37E

NMPM

LEA

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3352' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST / CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

INSTALL INJECTION PACKER PURSUANT TO NM UIC LETTER 12-01-99

Rig up on well, circulate oil blanket OOH.

POOH w/ 5 1/2" IPC tbg, Tag for fill.

GIH w/ workstring, make 2 bailor runs to extract fill (CaCO₄, acid soluble)

Spot surfactant on openhole face; swab back.

Spot 1500 gal 15% HCl on openhole face; swab back.

Repair wellhead: install new flange, bell nipple, SS valve.

Run 2 7/8" IPC J55 tbg. Set packer @ 3785'.

Notified OCD of MIT on 5-11-00, but no rep on site to witness. MIT at 380# for 30 min with no fall off. Chart attached.

Return to injection.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Carolyn Doran Haynes TITLE OPERATIONS ENGINEER DATE 5-15-00

Type or print name CAROLYN DORAN HAYNES

Telephone No. 505-393-9174

(This space for State use)

APPROVED BY _____ TITLE _____ DATE _____

Conditions of approval, if any:

5
C

BLINEBRY-DRINKARD SWD WELL A-22

817' FNL & 965' FEL, Sec 22, T22S, R37E, Lea County, New Mexico

KB ELEV is 3363'

GR ELEV is 3352'

300'

12 1/4" Hole

9 5/8" 36# Csg @ 321' w/250 sx C Cement

Cmt Circ to Surface

8 3/4" Hole

1200'

TBG: 132jts - 2 7/8" 6.5# J55 8rd IPC-505: 3785'

7" x 2 7/8" Full Bore Casing Packer @ 3785'

Set w/18 points tension

7" 20# Csg @ 3865' w/1300 sc "C"

TOC surface

5000'

TD 4965'

Drawn

BY

5/8/00

CDH

RICE OPERATING COMPANY

122 West Taylor

Hobbs, New Mexico 88240

BD SWD A-22

817' FNL & 965' FEL

SEC 22, T22S, R37E

Lea County New Mexico

