Submit 3 Copies to Appropriate District Office

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

Revised 1-1-89 District Office DISTRICT I OIL CONSERVATION DIVISION P.O. Box 1980, Hobbs NM 88241-1980 WELL API NO. 2040 Pacheco St. DISTRICT II 30-025-25255 Santa Fe, NM 87505 P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease STATE _ FEE X 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Lou Worthan 1. Type of Well: WELL WELL X OTHER 2. Name of Operator 8. Well No. Marathon 011 Company 14 3. Address of Operator 9. Pool name or Wildcat P.O. Box 2490 Hobbs, NM 88240 Wantz Abo 4. Well Location Unit Letter 520 North Feet From The 330 Line and Feet From The East Line Section 22-S Township Range 37-E **NMPM** Lea County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) GL 3350' KB 3361' 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data **NOTICE OF INTENTION TO:** SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON** CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER: OTHER: Plug Back, Complete Wantz Abo 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 4/10 MIRU pulling unit. POOH w/pump & rods. ND wellhead. NU BOP. POOH w/tbg. RIH w/gauge ring to 7200'. Set CIBP at 7140'. RIH w/pkr, test CIBP, OK. POOH w/pkr. Pump 1250 gals 15% acid. 4/12 Perforate 6556-60, 6565-69, 6580-84, 6608-14, 6621-24, 6655-66, 6680-84, 6719-27, 6736-42, 6747-51, 6755-62, 6881-84, 6957-59, 6964-68, 6969-71, 6975-77, 6978-79, 7011-13, 7043-45, 7052-54, 2 SPF, 230 holes. 4/13 RIH w/RBP & pkr. Acidize 6556-7054' w/12,300 gals 15% acid w/354 BS. Rel pkr and RBP, POOH. RIH w/pkr on 2 3/8" prod tbg. Set pkr at 6472'. Pull blanking plug. Flow to test tank. Set blanking plug. Rel on/off tool at 6468'. Install TIW valve. Made swab run. Pump 30 bbls 2% KCL water corrosion inhibitor. Latch onto on/off tool. Test tbg to 1000 psi. OK. ND BOP. NU wellhead. RIH. pulled blanking plug. Swab. 4/17 Open well to facilities. RD pulling unit. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE Records Processor 4/27/99 TYPE OR PRINT NAME Kelly TELEPHONE NO <u>393-7106</u> (This space for State Use) MILLIAMS APPROVED BY