

COPIES RECEIVED		
DISTRIBUTION		
SATISFACTION		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-934	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator EXXON CORPORATION	8. Farm or Lease Name NEW MEXICO "S" STATE
3. Address of Operator P.O. BOX 1600, MIDLAND, TEXAS 79701	9. Well No. 30
4. Location of Well UNIT LETTER I , 2160 FEET FROM THE SOUTH LINE AND 690 FEET FROM THE EAST LINE, SECTION 2 TOWNSHIP 22-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat DRINKARD - WANTZ GR WASH
15. Elevation (Show whether DF, RT, GR, etc.) TO BE FILED LATER	12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU RIG, SPUDDED 13 3/4" HOLE @ 12:01 AM, 8-29-76. DRILLED TO 1144' RAN 10 3/4" CSG (27 JTS) 51# K-55 SET @ 1144'. CMT W/570 SKS CL "C" W/1/4% GEL, 290 CACL2, TAILED W/100 SK CL "C" 2% CACL2. WOC 18 HRS, HELD OK. 8-30-76 DRILLED ON. 9-13-76 DRILLED TO 7180'. RAN 170 JTS 7" CSG 23# & 26# N-80 K-55, SET @ 7180'. CEMENTED W/400 SKS LITE WEIGHT CEMENT. 2ND STAGE CMT W/1000 SK LITE WEIGHT W/1/4# FLOCLE & 5# GILSONITE PER SK. TAILED W/400 SKS LITE WEIGHT, NO ADDITIVES. W.O.C. 18 HRS. CEMENT IN PLACE, GOOD RETURNS THROUGH OUT JOB. CEMENT HELD OK. 8-29-76, TESTED 10 3/4" CSG TO 300 AND 1000 P.S.I., 15 min, TESTED OK. 9-15-76, TESTED 7" CSG TO 300 AND 1500 P.S.I., 15 min, TESTED OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED **D. L. Climmer** TITLE **UNIT HEAD** DATE **10-1-76**

APPROVED BY _____ TITLE _____ DATE **001**

CONDITIONS OF APPROVAL, IF ANY: