

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SALE PRICE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR REPORT OF PRODUCTION, FOR OTHER PROPOSALS.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5a. Indicate Type of Lease State ☐ Fee ☒
2. Name of Operator Gulf Oil Corporation	5. State Oil & Gas Lease No.
3. Address of Operator Box 670, Hobbs, New Mexico 88240	7. Unit Agreement Name
4. Location of Well UNIT LETTER A 660 FEET FROM THE North LINE AND 990 FEET FROM East LINE, SECTION 30 TOWNSHIP 22-S RANGE 38-E	8. Form or Lease Name Vivian
	9. Well No. 11
	10. Field and Pool, or Wildcat Wantz Granite Wash
15. Elevation (Show whether DF, RT, GR, etc.) 3370' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7686' TD, 7640' PB

Reached total depth of 8-3/4" hole at 7686' at 10:00 PM, July 23, 1976. Ran 89 joints of 7" OD 26# K-55 ST&C casing, 89 joints of 7" OD 23# K-55 ST&C and 2 joints and 1 cut joint, of 7" OD 23# K-55 LT&C casing. Total of 180 joints and 1 cut joint, 7669'. Set casing at 7686' with DV tool at 2787'. Cemented thru shoe with 500 sacks of lite cement containing 6# salt and 1/4# flocele per sack and 425 sacks of Class C containing .5% CFR-2. Cement circulated. Cemented 2nd stage thru DV tool with 1000 sacks of lite cement containing 15# salt per sack and 75 sacks of Class C with 2% Ca Cl2. Cement circulated. WOC over 24 hours. Drilled DV tool and cleaned out to 7640'. Tested casing with 1500#, 30 minutes, OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>G.V. Berlin</u>	TITLE <u>Area Engineer</u>	DATE <u>August 2, 1976</u>
SEEN BY <u>Supv.</u>	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

JUE 21 1976

OIL CONSERVATION COMM.
HOBBS, N. M.