

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-032104

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

A.H. Blinebry Fed. NCT-1

9. WELL NO.

41

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 19, T-22-S, R-32-E

12. COUNTY OR PARISH

Lea

13. STATE
New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P. O. Box 728 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface Well is located 330' FSL & 2310' FEL of
Section 19, T-22-S, R-38-E, Unit Letter '0', Lea County,
New Mexico.

14. PERMIT NO.

Regular

15. ELEVATION: (Show whether DF, RT, GR, etc.)

3358' (GR)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Total Depth 7550'

13-3/8" OD 59.5# csg set @ 400'.

9-5/8" OD 36# K-55 Csg set @ 2902'

1. Ran 4888' (133 jts) 7" OD 23# and 26# N-80 & K-55 csg liner and set @ 7550'. Top of liner @ 2662'.
2. Cemented w/700 sx TLW containing 5# KCL & .3% Halad - 22/sx. & 300 sx Class 'H' Cement containing 5# KCL, .5% Halad-22 & 1/4# Flocele/sx. Job complete 12:15 P.M., 11-18-76. Cement circulated.
3. Tested top of 7" csg liner w/1000# for 1-hour, 4:15-5:15 P.M., 11-21-76. Tested O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Asst. Dist. Supt.

DATE 11-24-76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NOV 30 1976

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

SEP 7 1976

**OIL CONSERVATION COMM.
HOBBS, N. M.**