

5. LOCATION AND TYPE OF WATER SUPPLY:
  - A. Water for drilling will be purchased from Rowland Trucking, Eunice, and transported by truck to the wellsite. The well from which the brine water will be transported is located in the City of Eunice.
6. SOURCE OF CONSTRUCTION MATERIALS:
  - A. Caliche for surfacing the road and the well pad will be obtained from an existing pit in the SW/4 SE/4 Sec. 12 T-22S R-37E. It is a State caliche pit.
7. METHOD OF HANDLING WASTE DISPOSAL:
  - A. Drill cuttings will be disposed of in the drilling pits.
  - B. Drilling fluids will be allowed to evaporate in the drilling pits until pits are dry.
  - C. Water produced during tests will be disposed of in the drilling pits. Oil produced during tests will be stored in test tanks until sold.
  - D. Current laws and regulations pertaining to the disposal of human waste will be complied with.
  - E. Trash, waste paper, garbage, and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste material will be contained to prevent scattering by the wind. Location of trash pit is shown on Exhibit "C".
  - F. All trash and debris will be buried or removed from the well-site within 30 days after finishing drilling and/or completion operations.
8. ANCILLARY FACILITIES: None required.
9. WELLSITE LAYOUT:

Exhibit "C" shows the relative location and dimensions of the well pad, mud pits, reserve pit, trash pit, and location of major rig components.

  - B. Only minor levelling of the wellsite will be required. No significant cuts and fills will be necessary.
  - C. The reserve pit will be plastic lined.
  - D. The pad and pit area has been staked and flagged.
10. PLANS FOR RESTORATION OF THE SURFACE:
  - A. After completion of drilling and/or completion operations all equipment and other material not needed for operations will be removed. Pits will be filled and location cleaned of all trash and junk to leave the wellsite in an aesthetically pleasing condition as possible.
  - B. Any unguarded pits containing fluids will be fenced until they are filled.
  - C. After abandonment of the well, any special rehabilitation and/or revegetation requirements of the surface management agency will be complied with and accomplished as expeditiously as possible. All pits will be filled and levelled within 90 days after abandonment.

RECEIVED

NOV 10 1976

OIL CONSERVATION COMM.  
HOBBS, N. M.