

INSTRUCTIONS

This form is to be filed with the appropriate State Engineer of the Commission not later than 30 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All sections reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completion items, items 10 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required, (see Rule 11.2).

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____ 1180	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____ 1900	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____ 2800	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ -	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____ -	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____ -	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____ -	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ -	T. Simpson _____	T. Gallup _____	T. Ignacio Qute _____
T. Glorieta _____ 5152	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____ 5546	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____ 6147	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____ 6367	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____ 6922	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ 5540 _____ to _____ 5682 _____	No. 4, from _____ 7164 _____ to _____ 7216 _____
No. 2, from _____ 6140 _____ to _____ 6238 _____	No. 5, from _____ to _____
No. 3, from _____ 6470 _____ to _____ 6530 _____	No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ NONE _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	350	350	Surface rock gravel, sand				
350	1900	1550	Mainly Anhydrite				
1900	2800	900	Salt				
2800	3700	900	Anhydrite, lime				
3700	4400	700	Lime				
4400	5000	600	Lime, sand, dolomite				
5000	5100	100	Dolo., red bed, shale				
5100	5500	400	Dolo., anhydrite				
5500	6000	500	Dolomite, 10% shale				
6000	7550	1550	Dolomite, trace of shale, trace of anhydrite.				