

This form is not to
be used for reporting
packer leakage tests
in Northwest New Mexico

SOUTHEAST NEW MEXICO PACKER LEAKAGE TEST

Operator Exxon Company, U.S.A.			Lease New Mexico State 8			Well No. 37
LOCATION OF WELL	Unit C	Sec. 2	Twp. 22S	Rge. 37E	County Lea	
	NAME OF RESERVOIR OR POOL		TYPE OF PROD. (Oil or Gas)	METHOD OF PROD. FLOW, ART LIFT	PROD. MEDIUM (Tbg or Cag)	CHOKE SIZE
Upper Completion	Wantz Abo		Oil	Flowing	Tbg	32/64
Lower Completion	Wantz Granite Wash		Oil	Pumping	Tbg	64/64

FLOW TEST NO. 1

Both zones shut-in at (hour, date): 1300 hrs 4/5/87

Well opened at (hour, date): 1300 hrs 4/6/87

Indicate by (X) the zone producing

Pressure at beginning of test

Stabilized? (Yes or No)

Maximum pressure during test

Minimum pressure during test

Pressure at conclusion of test

Pressure change during test (Maximum minus Minimum)

Was pressure change an increase or a decrease?

Well closed at (hour, date): 1300 hrs 4/7/87

Total Time On
Production 24 hrs

Oil Production 3.0 bbls; Grav. 40.2

Gas Production 17 MCF; GOR 5667

Remarks:

FLOW TEST NO. 2

Well opened at (hour, date):	1400 hrs 4/8/87	Upper Completion	Lower Completion
Indicate by (X) the zone producing		X	
Pressure at beginning of test		320	5
Stabilized? (Yes or No)		No	No
Maximum pressure during test		320	10
Minimum pressure during test		50	Zero
Pressure at conclusion of test		50	Zero
Pressure change during test (Maximum minus Minimum)		270	10
Was pressure change an increase or a decrease?		Decrease	Decrease
Well closed at (hour, date):	1200 hrs 4/9/87	Total Time On Production	22 hrs
Oil Production During Test: --- bbls; Grav. ---		Gas Production During Test: ---	MCF; GOR ---

Remarks: _____

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

Approved: JUN 8 1987 19
New Mexico Oil Conservation DivisionBy: ORIGINAL-SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

Title: _____

Operator: EXXON CO. USA
By: Bruce R. Bellington
Title: ENGINEERING SUPERVISOR
Date: 5/28/87

SOUTHEAST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiple completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Office operation shall also be so notified.

3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized and for a minimum of two hours thereafter, provided however, that they need not remain shut-in more than 24 hours.

4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued until the flowing well-head pressure has become stabilized and for a minimum of two hours thereafter, provided however, that the flow test need not continue for more than 24 hours.

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the previously shut-in zone is produced.

7. All pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked with deadweight tester at least twice, once at the beginning and once at the end, of each flow test.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the appropriate District Office of the New Mexico Oil Conservation Division on Southeast New Mexico Packer Leakage Test Form Revised 11-01-78, together with the original pressure recording gauge charts with all the deadweight pressure readings which were taken indicated thereon. In lieu of filing the aforesaid charts, the operator may construct a pressure versus time curve for each zone of each test, indicating thereon all pressure changes which may be reflected by the gauge charts as well as all deadweight pressure readings which were taken. If the pressure curve is submitted, the original chart must be permanently filed in the operator's office. Form C-116 shall also accompany the Packer Leakage Test Form when the test period coincides with a gas-oil issue test period.

MAX
RECEIVED
OBS. OGD
1987