

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYCOPY TO 0.0.0.0
SUBMIT IN TRIPLICATE
(Other instructions on
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO. NM 25465
2. NAME OF OPERATOR BELCO PETROLEUM CORPORATION	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 10,000 Old Katy Road - Suite #100, Houston, Texas 77055	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FEL, 1980' FSL, Section 25	8. FARM OR LEASE NAME Federal BL 25
14. PERMIT NO.	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3636 GR	10. FIELD AND POOL, OR WILDCAT Undesig. Bell Lake Morrow
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 25, T23S-R33E
	12. COUNTY OR PARISH Lea
	13. STATE New Mexico

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud & surface casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

3/26/77 Spudded 26" hole.

3/30/77 Ran & set 18 jnts 20" 94# H-40 ST&C csg @ 703'; cmt'd w/748 sx Class "C" cement + 4% gel + 2% CaCl₂ + 1/4# Celloflakes, tailed in w/300 sx Class "C" + 2% CaCl₂ + 1/4# Celloflakes. No cmt to surface; plug down @ 3:00 a.m. on 3/31/77.3/31/77 Tagged cement @ 328' w/1" string; pumped 400 sx Class "C" cmt w/full returns; no cmt to surface; pumped 300 sx Class "C" cmt + 4% CaCl₂; circulated out 50 sx; Went in hole w/1 7/8" bit; drl'd 59' cut & shoe; found junk in hole.

4/1/77 Drld on junk.

4/2/77 Resumed formation drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Administrative Geologist

DATE

4/4/77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

APR 7 1977

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Consult local

Item 4: There are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include special information as is required by local Federal and/or State offices. In addition, each proposal and report should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid content; and sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site abandoned. Final inspection looking to approval of the abandonment.

GPO 680-379

RECEIVED

APR 12 1977

OIL CONSERVATION COMM.
HOBBS, N. M.

