

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SALE PRICE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDARY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PRODUCE TO BE LIFTED TO A DIFFERENT RESERVOIR, USE APPLICATION FOR REPORT - (FORM C-101) FOR SUCH PURPOSES.)		5a. Indicate Type of Lease State ☒ Fee ☐ 5. State Oil & Gas Lease No. L-1927
1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER- 2. Name of Operator GULF OIL CORPORATION 3. Address of Operator P. O. Box 670, Hobbs, NM 88240 4. Location of Well UNIT LETTER L 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 23-S RANGE 33-E NMPL.		7. Unit Agreement Name 8. Form of Lease Name Lea "RL" State 9. Well No. 1 10. Field and Pool, or Wildcat Brinninstool Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3695' GL		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐ TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒ PULL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOBS ☐ OTHER ☐ OTHER ☐		SUBSEQUENT REPORT OF:
---	--	---

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

15,950' TD. Displaced 10# Brine wtr with 11# mud. Spotted a 200' cement plug on top of pkr at 15,250' with Class H + .3% HR-12 cement. Spotted a 200' cement plug at 13,400' with Class H + .3% HR-12 cement. Spotted a 200' cement plug at 11,900' with Class H + .3% HR-2 cement. Ran a 7 5/8" CIBP and set at 11,700' and cap with 100' Class H + .3% HR-2 cement. Cut and pulled 7 5/8" casing from 986'. Spotted a 100' cement plug, Class C + 2% CaCl2 at 1050'. Cut and pulled 10 3/4" casing from 893'. Spotted a cement plug with Class C + 2% CaCl2 from 986' to 675'. Spotted a Class C and 2% CaCl2 cement plug from 100' to surface. Install Dry hole marker. Clean location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>H. B. Sikes, Jr.</i></u>	TITLE <u>Area Engineer</u>	DATE <u>5-23-78</u>
APPROVED BY <u><i>Eddie Lea</i></u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>MAY 28 1979</u>

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 25 1976

U. S. CONSERVATION COMM.
NORRIS, N. M.