

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L-1927

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101, FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation	8. Farm or Lease Name Lea "RI" State
3. Address of Operator Box 670 Hobbs, N.M. 88240	9. Well No. 1
4. Location of Well UNIT LETTER L 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 23-S RANGE 33-E N.M.P.M.	10. Field and Pool, or Wildcat Undes. Brinninstool Morr
15. Elevation (Show whether DF, RT, GR, etc.) 3695' GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

McVay Drilling Company spudded 17½" hole at 10:00 AM 5-8-77. Completed 17½" hole at 748' at 7:00 AM 5-9-77. Ran 17 Jts and 1 cut Jt 728' of 13 3/8" OD 48# H-40 ST&C casing.
Set and cemented at 748'. Cemented with 350 sacks of class C with 4% gel, 2% CA CL2, and 300 sacks class C with 2% CA CL2. Cement circulated. WOC cement 24 hours. Tested casing with 1250# for 30 minutes - OK.
Started drilling 12 1/4" hole at 748' at 2:15 PM 5-10-77.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>M. J. Borlin</u>	TITLE <u>Area Engineer</u>	DATE <u>5-11-77</u>
Orig. Signed By <u>John Runyan</u>	Geologist	
APPROVED BY <u>John Runyan</u>	TITLE <u>Geologist</u>	DATE <u>MAY 12 1977</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED
10-14-1977
U.S. DEPT. OF JUSTICE