



Mr. Perrin,

The following information is the survey data taken on the Chevron Drinkard B#5 horizontal well. If you have any questions please contact me at (915) 687-7950, if I am not in you may talk Jim Ward at that same number.

Thank you,

A handwritten signature in black ink that reads "Darron M. Anderson". The signature is fluid and cursive, with a long horizontal line extending from the end.

Darron M. Anderson
Drilling Representative

Chevron USA Inc.

Drinkard B #5-8 30-22S-38E

API# 30-625-25519

*** NAUTICAL (Version 2.0) ***

WELL: DRINKARD B #5

Target Az: 30.76

Closure Direction: 9

Target TVD: 6805

MD	INC	AZ	TVD	Vert. Section	Coordinates		Closure	Rate	Build	Walk	Tool
					N-S	E-W					Face
6657	0.4	329.0	6656.3	-12.0	4.3	-30.8	31.1				
6758	2.9	348.0	6757.3	-10.3	7.0	-31.9	32.6	0.03	0.19		
6763	7.5	348.0	6762.2	-10.0	7.4	-32.0	32.8	0.92	0.00		
6768	13.4	348.0	6767.2	-9.3	8.3	-32.2	33.2	1.18	0.00	0 R	
6773	20.0	348.0	6771.9	-8.2	9.7	-32.5	33.9	1.32	0.00	0 R	
6778	26.4	348.0	6776.5	-6.8	11.7	-32.9	34.9	1.28	0.00	0 R	
6783	33.0	348.2	6780.9	-5.0	14.1	-33.4	36.2	1.32	0.04	0 R	
6788	40.2	349.0	6784.9	-2.8	17.0	-34.0	38.0	1.44	0.16	0 R	
6793	46.3	348.4	6788.5	-0.2	20.4	-34.6	40.2	1.22	-0.12	0 R	
6798	52.9	348.9	6791.8	2.6	24.1	-35.4	42.8	1.32	0.10	0 R	
6803	59.3	349.7	6794.6	5.7	28.2	-36.2	45.9	1.28	0.16	0 R	
6808	65.1	350.3	6796.9	9.1	32.5	-36.9	49.2	1.16	0.12	0 R	
6813	72.2	352.6	6798.7	12.7	37.1	-37.6	52.9	1.42	0.46	0 R	
6818	77.9	355.8	6800.0	16.6	41.9	-38.1	56.7	1.14	0.64	0 R	
6823	82.9	0.4	6800.8	20.7	46.9	-38.3	60.5	1.00	0.92	45 R	
6828	85.6	2.8	6801.3	25.0	51.8	-38.1	64.4	0.54	0.48	45 R	
6833	86.6	4.1	6801.7	29.5	56.8	-37.8	68.3	0.20	0.26	45 R	
6838	87.5	4.6	6801.9	34.0	61.8	-37.5	72.3	0.18	0.10	30 R	
6843	88.3	4.9	6802.1	38.4	66.8	-37.0	76.4	0.16	0.06	30 R	
6848	88.9	5.4	6802.2	42.9	71.8	-36.6	80.6	0.12	0.10	75 R	
6853	89.4	5.9	6802.3	47.5	76.7	-36.1	84.8	0.10	0.10	45 R	
6858	89.7	6.4	6802.3	52.0	81.7	-35.6	89.1	0.06	0.10	60 R	
6863	89.9	7.2	6802.4	56.6	86.7	-35.0	93.5	0.04	0.16	75 R	
6868	90.3	7.7	6802.4	61.2	91.6	-34.3	97.9	0.08	0.10	75 R	
6873	90.5	8.3	6802.3	65.8	96.6	-33.6	102.3	0.04	0.12	75 R	
6878	90.7	8.9	6802.3	70.4	101.5	-32.9	106.7	0.04	0.12	80 R	
6883	90.9	9.4	6802.2	75.1	106.5	-32.1	111.2	0.04	0.10	85 R	
6888	91.1	9.9	6802.1	79.7	111.4	-31.3	115.7	0.04	0.10	90 R	
6893	91.3	10.4	6802.0	84.4	116.3	-30.4	120.2	0.04	0.10	95 R	
6898	91.2	10.8	6801.9	89.1	121.2	-29.5	124.8	-0.02	0.08	105 R	
6903	90.9	11.0	6801.8	93.8	126.1	-28.5	129.3	-0.06	0.04	115 R	
6908	90.3	11.0	6801.7	98.5	131.0	-27.6	133.9	-0.12	0.00	115 R	
6913	89.5	10.8	6801.8	103.2	136.0	-26.6	138.5	-0.16	-0.04	115 R	
6918	87.9	10.4	6801.9	107.9	140.9	-25.7	143.2	-0.32	-0.06	115 R	
6923	86.1	10.1	6802.1	112.6	145.8	-24.8	147.9	-0.36	-0.06	115 R	
6928	85.3	10.0	6802.5	117.2	150.7	-23.9	152.6	-0.16	-0.02	115 R	
6933	84.7	9.9	6802.9	121.9	155.6	-23.1	157.3	-0.12	-0.02	110 R	
6938	85.1	10.1	6803.4	126.6	160.5	-22.2	162.0	0.08	0.04	100 R	
6943	86.0	10.6	6803.8	131.2	165.4	-21.3	166.8	0.18	0.10	90 R	
6948	87.2	10.8	6804.1	135.9	170.3	-20.4	171.5	0.24	0.04	50 R	
6953	88.5	10.8	6804.3	140.6	175.2	-19.4	176.3	0.26	0.00	30 R	
6958	89.5	10.3	6804.3	145.3	180.1	-18.5	181.1	0.20	-0.10	15 R	
6963	90.8	8.9	6804.3	150.0	185.1	-17.7	185.9	0.26	-0.28	45 R	
6968	91.6	7.9	6804.2	154.6	190.0	-17.0	190.8	0.16	-0.20	60 R	
6973	92.6	7.0	6804.0	159.2	195.0	-16.3	195.6	0.20	-0.18	70 R	