

U. OF COPIES RECEIVED	
DISTRIBUTION	
ANYA FE	
FILE	
J.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDARY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSAL TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Sun Oil Company

Address of Operator
P. O. Box 1861 - Midland, TX 79702

Location of Well
UNIT LETTER **M** **330** FEET FROM THE **South** LINE AND **330** FEET FROM
THE **west** LINE, SECTION **1** TOWNSHIP **22S** RANGE **37E** N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3350.3 GR

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.
936209 A & B

7. Unit Agreement Name

8. Farm or Lease Name
Walter Lynch

9. Well No.
5

10. Field and Pool, or Wildcat
Wantz Granite Wash

12. County
Lea

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOBS ☒

OTHER ☐

SUBSEQUENT REPORT OF:

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-16 to
7-12-77

Drill to TD of 7897.

R & C 5-1/2 csg. (214 jts. 5-1/2 15.5# 1 K-55) CS 7897, FC 7873, DV tool 3994, Howco cmt thru shoe w/700 H POZ A 50/50 2% gel 0.5% CFR 2 5# salt disp. w/100 BFW 87 bbls. mud, plud did not bumb over disp. 15 bbls. shut down, FP 1200 psi, dropped bomb to open DV tool. Pumped 17 bbsl. mud 6 BPM start circ. 1200 spi, Circ. 55 bbls. mud, lost returns press 1200-400. Pumped additional 40 bbls. No circ. Howco mixed & cmtd thru DV tool w/530 sx Howco lite 15-1/2# Salt 3# gilsonite 1/4# FCL, TI w/100-C 3# salt, regained full returns after mixing cement. Displaced plug 2/87 BW FP 1200-2600, JC 8:15 PM Full returns while displacing plug: After bumping plug had no indication of leak off, shut csg in, WOC 6 hrs. Prep run Temp. Survey.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Carson M. Minter* TITLE Office Assistant DATE 8-3-77

APPROVED BY *Jerry S. [unclear]* TITLE DATE *8-10-77*

CONDITIONS OF APPROVAL *[unclear]*

RECEIVED

JUN 1977

OIL CONSERVATION COMM.
HOBBS, N. M.