

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYBUDGET BUREAU No. 12 R-124
(Other instructions on reverse side)

5. LEASE DESIGNATION AND SERIAL NO.

C 068848

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

American Quasar Petroleum Co. of New Mexico

3. ADDRESS OF OPERATOR

1000 MNB Tower, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FN & WL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3721' GL

7. UNIT AGREEMENT NAME

Brinninstool Unit

8. FARM OR LEASE NAME

Brinninstool Unit

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 21, T-23-S, R-33-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Casing cement record

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

7-6-77 TD 12,700 Ran 297 jts. 7 5/8" 39.#, 33.70#, & 46.10# S-95 casing. Set @ 12,700, Howco cemented 1st stage w/1120 sx Lite wt. & 300 sx Class H, opened DV tool @ 4981. Cemented 2nd stage w/580 sx Howco lite & 200 sx Class H. Cement did not circulate.

7-22-77 Ran DST #2 13,023 - 13,335 - Tool open. 5" PF w/str. blo. GTS in 4" SI 90" op 2' FF 100# on 1/4" ck in 15", op 1/2" ck in 1' 45" 75.# decr to 2#, stab last 30", 4' SI rec. 660' DF, splr 1750 psi, 10.54 cfg w/tr Fluid. IHP-7642, IFP-489, 90" ISIP 3802, FFP 489, 4' FSIP-9018 FHP-7642, BHT 260°F

18. I hereby certify that the foregoing is true and correct

SIGNED

Jesse B. Munneley

TITLE Division Engineer

DATE August 11, 1977

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side

APPROVED

AUG 15 1977

BERNARD MOROZ
ACTING DISTRICT ENGINEER

1977
OIL CONSERVATION COM.
HOBBS, N. M.