

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on
reverse side)

COPY TO O.E.C.

Form approved,
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

American Quasar Petroleum Co. of New Mexico

3. ADDRESS OF OPERATOR

1000 Midland National Bank Tower, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FN & WL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3721 G.L.

5. LEASE DESIGNATION AND SERIAL NO.

LC 068848

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Brinninstool Unit

8. FARM OR LEASE NAME

Brinninstool Unit

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Brinninstool Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 21

T-23S, R-33E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing cement record

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-10-77 TD 5195', ran 120 joints of 10 3/4", 51 lbs S95 new casing, set @ 5195'.
HOWCO cemented with 950 sx Lite and 300 sx class "C". Top cement by
temperature survey @ 1375'.

6-17-77 Ran DST #1, 7418-7645'. Recovered 590' drilling mud.

RECEIVED
JUL 1 1977
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

R. L. Sullivan

TITLE Division Operations Manager

DATE 6/30/77

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD
JUL 1 1977
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

RECEIVED

JUL 12 1957

CL CONSTITUTIONAL
HOBBS, N. M.