·				1 ( <sup>1</sup>	
NO. OF COPIES RECEIVED					
DISTRIBUTION	NEW MEXICO OIL CONSE	ERVATION COMMISSIC	)N F	orm C-101 levised 1-1-65	
SANTA FE					Type of Lease
FILE				STATE	I
U.S.G.S.					Gas Leuse No.
LAND OFFICE					
OPERATOR				mm	anni anna
	DUIT TO DOUL DEEDEN			///////	
	RMIT TO DRILL, DEEPEN,	UK FLUG DACK		7. Unit Agree	ment Name
1a. Type of Work					
b. Type of Well	DEEPEN	PLUG	васк 🔄 占	8. Farm or Le	ase Name
		SINGLE K	ZONE	Drink	ard (NCT-B)
OIL X GAS UELL OTH	ER			9. Well No.	
Gulf Oil Corporation				6	)
3. Address of Operator		······		10, Field and	Pool, or Wildcat
Box 670 Hobbs, NM 88240		G		Wantz Gr	anite Wash
4. Location of Well UNIT LETTER P	LOCATED 660	FEET FROM THE SOU	th		
UNIT LETTER		<u> </u>	l l		
AND 860 FEET FROM THE Ea	ast Line of Sec. 30	TWP. 22-S RGE.	38-E NMPM	111111	
				12. County	
			IIIIII	Lea	<i>{}}}}}}}</i>
(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)			19A, Formation	7/1/1/	20. Rotary or C.T.
		19. Proposed Depth			
<u>(</u> [[]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]]		7650'	Granite		Rotary Date Work will start
21. Elevations (Show whether DF, RT, etc.)	21A, Kind & Status Plug, Bond	213. Drilling Contracto:			
3368' GL	Blanket			July	20, 1977
23.	PROPOSED CASING A	ND CEMENT PROGRAM			

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
122	8 5/8"	24#	1230'	Circulate	
7 7/8"	5 1/2"	15.50#	7650' *	Circulate	
			│ * Will set DV	tool at approx	. 3000' and

.

Circulate cement.

.

BOP: See drawing No 3 attached.

.

!

APPROVAL VALID FOR 90 DAYS UNLESS DRILLING COMMENCED EXPIRES	77
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	× 1 10 1077
Signed (I Area Production Manager	DateJuly_13, 1977
APPROVED BY CTELL CONTON TITLE	DATE
CONDITIONS OF APPERDVAL, IF ANY	

CIL COMSERVATION COMM. HOBBS, N. M.

,



3000 PSI WORKING PRESSURE BLOWOUT PREVENTER HOOK-UP

The blowout preventor assembly shall consist of one blind ram preventer and one pipe ram preventer, both hydroulically operated; a flydrii "CK" preventer; valves; chokes and connections as illustrated. If a topored drill string is used, a ram preventer must be provided for each size of drill pipe. Casing and tubing roms to fit the preventers are to be available as needed. If correct in size, the flanged outlets of the ram preventer may be used for connecting to the 4-inch 1.D. choke flow the and kill line, except when air or gas drilling. The substructure height shall be sufficient to install a rotating blowout preventer.

Minimum operating aquipment for the preventers and hydraulically operated valves shall be as follows: (1) Multiple pumps, driven by a continu-ous source of power, capable of fluid charging the total accumulator volume from the nitrogen procharge pressure to its rated pressure within \_\_\_\_\_minutes. Also, the pumps are to be connected to the hydraulic operating system which is to be a closed system. (2) Accumulators with

a precharge of nitrogen of not less than 750 PSI and connected so as to receive the aforementioned fluid charge. With the charging pumps shut down, the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close all the pressure shall be not less than 1000 PSI accumulators must be sufficient to close accumulators accumulators must be sufficient to close accumulators must be sufficient pumps; or there shall be additional pumps operated by separate power and equal in pertormance capabilities. the remaining accumulator fluid volume at least percent of the original. (3) When requested, an additional source of power, ramote and equivalent, is to be available to operate the above seconds: after closure, the remaining accumulator pressure shall be not less than 1000 PS1 with

The closing numifold and remote closing manifold shall have a separate control for each pressure-operated device. Controls are to be labeled, with control handles indicating open and closed positions. A pressure reducer and regulator must be provided for operating the Hydrill preventer. <u>When requested</u>, a second pressure reducer shall be available to limit operating fluid pressures to ram preventers. Guif Legion No.38 hydroulic oil, an equivalent or better, is to be used as the fluid to operate the hydraulic equipment.

and without sharp bends. Easy and safe access is to be maintained to the choke manifold. All valves are to be selected for operation in the presence of all, gas, and drilling f unds. The choke flow line valves connected to the drilling spool and all ram type preventers must be equipped with stem extensions, universal joints if needed, and hand wheels which are to extend beyond the edge of The choke manifold, choke flow line, and choke lines are to be supported by metal stands and adequately anchored. The choke flow line and choke lines shall be constructed as straight as possible the derrick substructure. All other valves are to be equipped with handles.

\* To include derrick floor mounted controls.

## NEW COLOUR NSERVICE OF AN AND ACREASE AND THE SERVICE OF A SERVICE OF

••• ·

ŧ.

,

GULI	FOIL CORF	p,		DRINKAR	D NCT-B	6
	30	<b>2</b> 2 S	outh	38 East	Leo	
660	n an	South	··· ·	860	East	
3368.1	Grani	te Wash			ash	40
L Outland	en e	lan en trocher en t		A LA STRACT OF	No. I the second s	
	that oue isa≂€ and ioyalts)	e prodestan a state	the set is	alise east a stil	the first of the second se	to to get the second
3. Honore in diated by	san one lease - connunitizità	uf tillsteid owaev all applyzation för	- n : 13	late <sup>t</sup> te trouvel ∈to <sup>9</sup>	an a	
Nes.	5 × 10	H. ABARTAS TARS	• • • • •	asoldat a	-	
S1 11	a the second second	algaed to the well approved and the second		ereste base te la di, elucitat pres		
				ب ، دور در با مریونی ۱۹۹۹ - ۱۹۰۱ - مریو میرونی	· · · · · · · · · · · · · · · · · · · ·	
	:					
					CER	mand
	;		a	.m. 14	C. D. BORL	rland
	: • - •			<b>10 1</b>	C. D. BORL	
	•			• • • • • • • • • • • • • • • • • • •	Area Produ	ction Manager
	: 				Area Produ Gulf Oil C	ction Manager orporation
	: • • • •				Area Produ	ction Manager orporation
	: 				Area Produ Gulf Oil C	ction Manager orporation
· · · · ·					Area Produ Gulf Oil C	ction Manager orporation
					Area Produ Gulf Oil C	ction Manager orporation
				· · · · · · · · · · · · · · · · · · ·	Area Produ Gulf Oil C	ction Manager orporation
				· · · · · · · · · · · · · · · · · · ·	Area Produ Gulf Oil C July 13, 1	ction Manager orporation

and the second sec

JUL 1- 1917

CIL CONSERVATION COMM. HOBBS, N. M.

a service and 

,