



© - copyrighted Reproduction Prohibited

IP (Drinkard) Perfs 6429-6598' F 67 BOPD + 66 BW. Pot based
on 24 hr test thru 24/64" chk. GOR 14,343; gty 39.4; CP Pkr;
TP 400#

CONTR MGF #10 OPRS ELEV 3432' GL "D 6750' RT

F.R. 8-8-77
(Drinkard)
8-17-77 Drlg 4485'
8-22-77 Drlg 6542'
8-29-77 TD 6700'; WOC
9-2-77 TD 6700'; PBD 6671'; Tstg
Perf (DRKD) 6429-31', 6470-72', 6523-25',
6558-60', 6596-98' w/2 SPF
Acid (6429-6598') 2600 gals
9-12-77 TD 6700'; PBD 6671'; SI
Flwd 132 BO + 17 BW in 32 hrs thru 18/64" chk
(6429-6598')
9-26-77 TD 6700'; PBD 6671'; Complete
LOG TOPS: Rustler Anhydrite 1114', Salt 1211',
Base Salt 2428', Yates 2592', Seven Rivers
2853', Queen 3307', Grayburg 3600', San Andres
3868', Glorieta 5084', Blinbry 5412', Tubb 6112',
10-1-15 NM

LEA
GULF OIL CORP.

Drinkard NM
12 Christmas, A. L. NCT-C Page #2
Sec 18, T22S, R37E

9-26-77 Continued
Drinkard 6419'
10-1-77 COMPLETION ISSUED

10-1-15 NM
IC 30-025-70207-77