

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator Marathon Oil Company		8. Farm or Lease Name Walter Lynch	
3. Address of Operator P. O. Box 2409, Hobbs, New Mexico		9. Well No. 8	
4. Location of Well UNIT LETTER <u>E</u> <u>1880</u> FEET FROM THE <u>North</u> LINE AND <u>760</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>22-S</u> RANGE <u>37-E</u> N.M.P.M.		10. Field and Pool, or Wildcat Wantz Granite Wash	
15. Elevation (Show whether DF, RT, GR, etc.) 3356' GR		12. County Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Spudded 12 1/4" hole at 11:15 A.M., September 10, 1977.
- Drilled 12 1/4" hole to 1246'.
- Set 9 5/8", 36#, H-40 at 1246'.
- Cemented with 300 sacks of Lite containing 5# of Gilsonite, 5# salt and 1/4# Flocele per sack. Tailed in with 300 sacks of Class "C" containing 2% Ca Cl. Cement circulated.
- W.O.C. for 12 hours, cut off casing and installed B.O.P's.
- Tested casing and B.O.P'S to 1500psi, for 30 minutes. Held OK.
- W.O.C. 28 hours. Commenced drilling 8 3/4" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Anthony Kovacs TITLE Production Engineer DATE 9-23-77

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

SEP 23 1977