

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
SEE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>S &amp; D Partnership</b>	8. Farm or Lease Name <b>Drinkard Homestead</b>
3. Address of Operator <b>Drawer 309, Hobbs, NM 88240</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>C</b> <b>660</b> FEET FROM THE <b>North</b> LINE AND <b>2310</b> FEET FROM THE <b>West</b> LINE, SECTION <b>25</b> TOWNSHIP <b>22 S</b> RANGE <b>37 E</b> N.M.P.M.	10. Field and Pool, or Wildcat <b>Wantz Granite Wash</b>
11. Elevation (Show whether DF, RT, GR, etc.) <b>3304.5 GL</b>	12. County <b>Lea</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <b>Perforating &amp; acidizing</b> <input checked="" type="checkbox"/>

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled out DV Tool @ 4455'. Drilled float collar & cement to 7802'. Perforated 4 1/2" csg as follows: 2 shots per foot @ 7486, 7493, 7501, 7521, 7535, 7544, 7553, 7617, 7626, 7655, 7683, 7711, 7717; 1 shot per foot @ 7729, 7734, 7737, 7746, 7757, 7763, 7771, 7775.

Acidized perfs w/2000 gal 15% NE-EE acid.

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Elise Spear* TITLE **Partner** DATE **1/29/79**

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE **FEB 2 1979**

CONDITIONS OF APPROVAL, IF ANY: