

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <u>Summit Energy, Inc.</u>	8. Farm or Lease Name <u>Drinkard Estate</u>
3. Address of Operator <u>112 N. First Street, Artesia, New Mexico 88210</u>	9. Well No. <u>7</u>
4. Location of Well UNIT LETTER <u>H</u> , <u>1980</u> FEET FROM THE <u>NORTH</u> LINE AND <u>990</u> FEET FROM THE <u>EAST</u> LINE, SECTION <u>25</u> TOWNSHIP <u>22</u> RANGE <u>37</u> NMPM.	10. Field and Pool, or Wildcat <u>Wantz Granite Wash</u>
15. Elevation (Show whether DF, RT, GR, etc.) <u>3314.6</u>	12. County <u>Lea</u>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 1200'. Circulated 1 hour, Rigged up and ran 30 jts. of 8 5/8"-24#-J55S casing to 1200'. Cemented with 260 sacks HOWCO Lite with 2% CaCl plus 200 sacks Class "C" with 2% CaCl. Circulated out 75 sacks. Plug down at 5:00 a.m. (1-10-78). After 24 hours tested casing to 1500 psi for 30 minutes - held O.K. Drilled plug and tested casing to 1500 psi for 30 minutes. Held O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Paul White TITLE Vice President-Production DATE 1-11-78

Orig. Signed by

Jerry Sexton

Dist 1, Supv.

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

JAN 13 1978

RECEIVED

JAN 12 1978

OIL CONSERVATION COMM.
HOBBS, N. M.