35-62 - 23177

1). OF COPIES RECEIVED							
	DISTRIBUTION NEW MEXICO OIL CONSERVATION COMMISSION						
ANTA FE					Form C-101 Revised 1-1-65		
FILE		-				5A. Indicate Type of Lease	
U.S.G.S.					STATE	FEE K	
LAND OFFICE					.5. State Oil	& Gas Lease No.	
OPERATOR							
					111111		
APPLICATIO	N FOR PERMIT TO	DRILL, DEEPEN, C	OR PLUG BACK				
1a. Type of Work					7. Unit Agre	ement Name	
DRILL X		DEEPEN [PLUG	BACK			
b. Type of Well					8. Farm or L	.ease Name	
OIL GAS X	OTHER	·	SINGLE X MUL	ZONE		Christmas (NCT-A)	
2. Name of Operator				-	9. Well No.		
Gulf Oil Cor	poration				10		
3. Address of Operator						10. Field and Pool, or Wildcat	
P. O. Box 670, Hobbs, NM 88240					Jalma	t Gas	
4. Location of Well UNIT LETTE	B Loc	ATED 810 FE	EET FROM THE North	LINE			
AND 1830 FEET FROM	THE East LIN	E OF SEC. 27 TV	VP. 22-S RGE.	36-E HMPM	7777777		
					12. County		
				HHH	Lea	WHIHHAM.	
			9. Proposed Depth	A Formation	7777777		
		, (((((((((((((((((((((((((((((((((((((9A. Formation	~ "	20. Rotary or C.T.	
21. Elevations (Show whether DF)			3650'	Jalmat	7/	Rotary	
		1	1B. Drilling Contractor		22. Approx	c. Date Work will start	
3512' GL	Blan	nket L					
23.	P	ROPOSED CASING AND	CEMENT PROGRAM		¥		
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF	CEMENT	EST. TOP	
12 1/4"	8 5/8"	24#	3001	circ			
7 7/8"	4 1/2"	9.50#	3650 '	circ			
	ı		1	•		1	
Note: See a	ttached BOP Drav	ving #3					
Mada Ol	2001	3					
	300' - Spud 3650' - Brine	mud e water with Po	1yomer- 10# wt				
			-		. in		
					OVAL VALID	¢SS	
APP FOR DRILLI EXPIRES					DAYS UNI	JCED,	
		<u></u>		FOR GO	COMME	1978	
		<u> </u>		DRILLIA	a	1970	
		1 1			July Dr	and the same of th	
				-VOIRES #			
				EVILLE			
				,			
IN ABOVE SPACE DESCRIBE PE	ROPOSED PROGRAM: IF	PROPOSAL IS TO DEEPEN OF	R PLUG BACK, GIVE DATA O	N PRESENT PR	ODUCTIVE ZONI	E AND PROPOSED NEW PRODUC-	
TIVE ZONE. GIVE BLOWOUT PREVENT		olete to the best of my kn	owledge and belief.				
100 15 Km					~ -	70	
Signed ()	aual	Title Area Prod	uction Manager		Date <u>3-8</u>	- 78	
(This space for	State Use)	Geologial			M		
APPROVED BY JAM W	· / Wingan	TITLE			DATE	H	
CONDITIONS OF APPROVAL, IF	ANY:						

R MARKED

LUNE 9 1578

OIL COUSTINATION COMM.

Revised April, . 1971 Fill Line Connection Check Valve Emergency Kill L'ne Floor Manifold onnect To Check Valve 2" Kill Line Hydril"GK" Drilling Casing Head Spool Roms Roms ę As an Alternate: The Kill & Relief Connections From The Casing Spool May Be Connected To The Flanged Outlets Of The Bottom Ram Preventer. To Choke Manifold Hydrautically Operated Va:ve FlowLine To Reserve Flow Line Choke \mathbb{Z} 29/6 Beyond Edge of Derrick Floor 2"Chokes To Reserve Pit & Choke Boxes See Choke Manifold ₆" Minimum Bore — Detail Below 4" I D. Choki Flow Line CHOKE MANIFOLD DETAIL To Casing Spool Hydraulically Operated Valve
 When Specified Straight To To Mud Pit &
Reserve Pit
It Line From Spool
Reserve Pit *Pressure
Operated Choke
When Requested
or Specified ADDITIONS - DELETIONS -SPECIFY CHANGES

DRAWING NO.3

3000 PSI WORKING PRESSURE BLOWOUT PREVENTER HOOK-UP

The blowout preventer assembly shall consist of one blind ram preventer and one pipe ram preventer, both hydraulically operated; a Hydril "GK" preventer; valves; chokes and connections as illustrated. If a topered drill string is used, a ram preventer must be provided for each size of drill pipe. Casing and tubing rams to fit the preventers are to be available as needed. If correct in size, the flanged outlets of the ram preventer may be used for connecting to the 4-inch I.D. choke flow one and kill I ne, except when air or gas drilling. The substructure height shall be sufficient to install a rotating blowout preventer.

ous source of power, capable of fluid charging the total accumulator volume from the nitrogen precharge pressure to its rated pressure within Minimum operating equipment for the preventers and hydraulically operated valves shall be as follows: (1) Multiple pumps, driven by a continuminutes. Also, the pumps are to be connected to the hydraulic operating system which is to be a closed system. (2) Accumulators with

a precharge of nitrogen of not less than 750 PSI and connected so as to receive the aforementioned fluid charge. With the charging pumps shut down, the pressurized fluid volume stored in the pumps; or there shall be additional pumps operated by separate power and equal in performance capabilities. the remaining accumulator fluid volume at least accumulators must be sufficient to close all the pressure-operated devices simultaneously within __percent of the original. (3) When requested, an additional source of power, remote and equivalent, is to be available to operate the above _seconds; after closure, the remaining accumulator pressure shall be not less than 1000 PSI with

The closing manifold and remote closing manifold shall have a separate control for each pressure-operated device. Controls are to be labeled, with control handles indicating open and closed positions. A pressure reducer and regulator must be provided for operating the Hydril preventer. When requested, a second pressure reducer shall be available to limit operating fluid pressures to ram preventers. Gulf Legion No.38 hydraulic oil, an equivalent or better, is to be used as the fluid to operate the hydraulic equipment.

and without sharp bends. Easy and safe access is to be maintained to the choke manifold. All valves are to be selected for operation in the presence of oil, gas, and drilling fluids. The choke flow line valves connected to the drilling spool and all ram type preventers must be equipped with stem extensions, universal joints if needed, and hand wheels which are to extend beyond the edge of the derrick substructure. All other valves are to be equipped with handles. The choke manifold, choke flow line, and choke lines are to be supported by metal stands and adequately anchored. The choke flow line and choke lines shall be constructed as straight as possible

* To include derrick floor mounted controls.

NEW SICO OIL CONSERVATION COMMISSION WELL LATION AND ACREAGE DEDICATION ⊢LAT

Form C-102 Supersedes C-12. Effective 1-1-65

Ronald J. Eidson

3239

\$1475.37 Y Gulf Oil Company A.L. Christmas NCT-A 10 22 South 36 East Lea ing Trictage Location of Webs 810 1830 North East feet from the ane and and . gver Elev Producing Formation Designated Accesses 3512.0 Jalmat Jalmat Gas 160 1 Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and rovalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc? If answer is "yes," type of consolidation _ If answer is "no," list the owners and tract descriptions which have actually been consolidated. (I se reverse side of this form if necessary.)_ No allowable will be assigned to the well until all interests have been consolidated the communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commis-CERTIFICATION I hereby certify that the information contained herein is true and complete to the C. D. Borland Area Production Manager Gulf Oil Corporation 3-8-78 i heraby certify that the well location shown on this plat was plotted from field Feb. 27, 1978 John W. 676

ECCENTED)

EAR 91978

OIL CONSERVATION CUMM.