

NEW MEXICO OIL CONSERVATION COMMISSION

N. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator GULF OIL CORPORATION	8. Farm or Lease Name Hugh
3. Address of Operator P. O. Box 670, Hobbs, New Mexico 88240	9. Well No. 13
4. Location of Well UNIT LETTER <u>A</u> <u>710</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>14</u> TOWNSHIP <u>22-S</u> RANGE <u>37-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Wantz Granite Wash
15. Elevation (Show whether DF, RT, GR, etc.) 3338' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

M-G-F Drilling Company Rig #10 spudded a 12-1/4" hole @ 4:30 P.M., 7-26-78.
Reached TD of 12-1/4" hole @ 10:15 A.M., 7-27-78. Ran 29 joints (1123.95') of
8-5/8" 24# K-55 ST&C casing. Set @ 1137'. Set insert float @ 1100'. Cement
with 300 sacks of Class "C" w/6% gel + 200 sacks of Class "C" w/2% CaCl₂. Plug
down @ 4:45 P.M., 7-27-78. Cement circulated. WOC 18 hours.

Tested 8-5/8" casing to 1500# for 30 minutes; held o.k.

Began drilling 7-7/8" hole @ 11:00 A.M., 7-28-78.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Glyn Stone TITLE Acting Area Engineer DATE 7-31-78

APPROVED BY Jerry Sexton TITLE Dist. 1, Super DATE AUG 1 1978

CONDITIONS OF APPROVAL, IF ANY: