

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
P.O. Drawer "A", Levelland, Texas 79336

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980 FSL & 660 FWL, Sec 26,  
AT TOP PROD. INTERVAL: (Unit L, NW $\frac{1}{4}$ , SW $\frac{1}{4}$ )  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Set Liner

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED

DEC 8 1978

U. S. GEOLOGICAL SURVEY

HOBBO, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to TD 15,808' and on 11-20-78 ran 5" 17.93# N-80 liner set at 15,807'. Top of the liner set at 11,897'. Cemented with 400 sx. Class H cement plus additives. Circulated cement. WOC 12 hours. Drilled cement 11,667'-11,897'. WOC 29 hrs. Test casing 1000# for 30 minutes. Test O.K. Released rig 4:00 p.m. 11-22-78.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dennis Evans TITLE Assist. Admin. Analyst DATE 12-6-78

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

0+4-USGS 1-Southland Royalty  
1-Houston 1100 Wall Tower West  
1-Susp Midland, TX 79701  
1-DE

\*See Instructions on Reverse Side

