

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	B-1167

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Doyle Hartman	8. Farm or Lease Name Highland State
3. Address of Operator 508 C & K Petroleum Bldg. Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>J</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>16</u> TOWNSHIP <u>23-S</u> RANGE <u>36-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Jalmat
15. Elevation (Show whether DF, RT, GR, etc.) 3424 G. L.	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled well to a total depth of 3450 RKB. Ran 94 jts (3464 ft) of 5 1/2 OD, 14 lb/ft, J-55, ST&C casing and landed at 3450 RKB. Cemented casing with 300 sx of API Class-C cement containing 3% Halliburton Econolite, 5 lb/sx Gilsonite, and 1/4 lb/sx Floccel followed by 350 sx of a 50-50 blend of API Class-C cement and Pozmix "A" containing 18% salt, 5 lb/sx gilsonite, and 1/4 lb/sx Floccel. Plug down at 11:00 AM CDT 6-19-78. Circulated 185 sx of excess cement to pit. Pressure tested casing to 1500 psi. Pressure held okay.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Doyle Hartman TITLE Operator-Part Owner DATE 7-17-78

APPROVED BY Don L. Goy TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: