

10/2/80

COPY TO O. G. C.

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other P&A
2. NAME OF OPERATOR
Conoco Inc.
3. ADDRESS OF OPERATOR
P.O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 1980' FEL
AT TOP PROD. INTERVAL: ☒
AT TOTAL DEPTH: ☒
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
LC-068848
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Brinninstool Unit
8. FARM OR LEASE NAME
Brinninstool Unit
9. WELL NO.
3
10. FIELD OR WJLDCAT NAME
Und. Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 19, T-23S, R-33E
12. COUNTY OR PARISH
Lea
13. STATE
N.M.
14. API NO.
30-025-26034
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3697' GR

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

OCT 27 1979

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-28-79 POOH W/ pkr. & tbg. Dumped 8 sx. class "H" cmt. w/ additives on top of CIBP @ 10,580'. Set cmt. retainer @ 9366'. Pumped 100 sx. class "H" cmt. w/ additives through retainer. Dumped 10 sx. of cmt. on top of retainer. Circ. hole clean. Shot off 7 5/8" csq. @ 6677'. Recovered 158 jts. Spotted 50 sx. class "C" cmt. plug @ 6752'. TOC @ 6556'. Spotted 40 sx. class "C" cmt. plug @ 5147'. TOC @ 5050'. Spotted 41-sack class "C" cmt. plugs @ 4960' & 1520'. Set cmt. plug from 50' to surface. Erected dry hole marker 12-15-79.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Butterfield TITLE Admin. Supervisor DATE 12/21/79

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE ACTING DISTRICT ENGINEER DATE OCT 17 1980

CONDITIONS OF APPROVAL, IF ANY:

4365-5
FILE