

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator MARTINDALE PETROLEUM CORPORATION		8. Farm or Lease Name Little "V"
3. Address of Operator P. O. Box 2955 Hobbs, NM 88240		9. Well No. 2
4. Location of Well UNIT LETTER D 330 FEET FROM THE South LINE AND 480 FEET FROM THE West LINE, SECTION 7 TOWNSHIP 22S RANGE 37E NMPM.		10. Field and Pool, or Wildcat Drinkard
15. Elevation (Show whether DF, RT, GR, etc.) 3435.1 GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 8:00 pm 11/26/78

11/30/78 Ran 1149' 8 5/8" new 24#/ft K-55 casing, set @ 1108'.

Cemented w/ 275 sx Halliburton lite cement W/ 5#/sx salt + 1#/sx floccle
300 sx Class "C" cement w/ 2% BaCl. Cir. approximately 100 sx.

Plug down 4:55 pm

12/1/78 Tested 8 5/8" surface casing w/ 1000psi for 30 minutes, no pressure decline.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Jo Johnson* TITLE Secretary-Treasurer DATE Dec. 4, 1978

APPROVED BY Orig. Signed by Jerry Sexton TITLE DATE DEC - 6 1978

CONDITIONS OF APPROVAL, IF ANY: None