

CASING, CENTRALIZERS & SCRATCHERS

LIST TYPE OF STRING BY CODE LETTERS, i.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINER (L); PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)

FROM-TO	OD	DRIFT ID	WT PER FT	GRADE	THREAD	ANT	WT. IN AIR, WT. IN MUD		REMARKS
							1000 LBS	1000 LBS	
(S) 0' - 1600'	8 5/8"	7.972"	24.00	K-55	STC	1600'	38.4		
(P) 0' - 3880'	5 1/2"	4.825"	15.50	K-55	STC	3880'	60.2		Sand blast bottom 30'

TYPE OF STRING

TYPE OF STRING	CENTRALIZERS		SCRATCHER	OTHER ACCESSORY EQUIPMENT		REMARKS
	INTERVAL	NO. FROM-TO		(SUCH AS DEGASSERS, MUD. CENTRIFUGE	FLOAT COLLARS, ETC.; - SPECIFY)	
(S) Surface	100' Spacing (16) 0'-1600'	15' Spacing None		Guide shoe and float collar		
(P) Production	(2) 1450'-1550' (above 8 5/8" shoe)	(22) 3550'-3880'		Float shoe and float collar		
	(9) 3520-3880' (over pay zone)	15' spacing (over pay zone)				