

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
a	double upset bolt s/aq. nut, round washer, and cotter key on short end, sq. nut and wf locknut on long end, 1 1/8" long. (or length required.)	7628			
b	wet process porcelain secondary spool insulator, 3" - brown, glass		1101		
d	regulated size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. Dwg ES-18 Note: provide clamp and ground conduit			BURBURY SERIES "UC"	
e	parallel groove clamp, size req'd				
f	secondary insulator clevis for 4" insulator	6510			
g	5/8" thimble nut	5512			
h	5/8" x 12" for length req'd straight thimble			ALUMINUM 6M3-6	
j	bolt w/aq. nut			ALUMINUM 15M3-6	X
l	transformer cluster mount bracket (large)				
m	req'd size raintight disconnect & fuses, 3-phase, 600 V. Ref. Dwg No. ES-19				
n	16" cross plate anchor (or size req'd)	X-16			
q	8-way expanding anchor (size req'd)	88135			
r	4" brown glass wet process porcelain secondary spool insulator		10101		
u	5/8" x 7" thimble anchor rod w/nut (use twineye if req'd - Chance No. 3347)	5317 (NUT 55006P)			
aa	3/8" high strength guy strand (10,800 lb.)				
bb	preformed guy grip for 3/8" guy strand	5010			
dd	5/8" x 10" angle thimble bolt w/nut	6813 1/2			X
ee	3"x3"x1/4"x11/16" hole curved washer				
ff	6" - guy clamp w/3-1/2" bolts				
gg	medium size strain insulator	6454			
hh	sec'ing sleeve for 3/8" guy strand	7867			X
jj	3/16" x 2-1/2" x 7" lift plate				
nn	pole bottom ground plate (may use butc-wrapp if desired)				
qq	Ground connection (See Dwg. ES-12)				
rr	wet process porcelain secondary spool insulator, 3" - white, glass				
tt	wet process porcelain secondary spool insulator, 4" - white, glass				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		<div style="text-align: center;"> CONOCO HOBS DIVISION DRAWING NO. ES-17 SHEET 5 OF 5 </div>	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB: FILE 5715	