

ITEM	DESCRIPTION	A. B. QUANCE NO.	JOSLYN NO.	OTHER PERS. NO.	NO. SUB.
A	35' class 6 creosoted pine pole				
B	3 1/2" x 4 1/2" x 8' treated creosotum				
C	High density wet process porcelain pin insulator		463		
D	5/8" x 3" forged steel pin w/eq. washer, nut, & locknut	081			
E	5/8" x 13" machine bolt w/ nut (or length req'd)	8812			
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole sq. washer	6813			
G	5/8" HF Locknut	3512			
H	1/8" x 1 1/4" x 28" flat creosotum brace	7128			
J	1/8" x 4 1/2" Feller Drive Log Screw	506754			
K	3/8" x 4 1/2" Carriage Bolt w/ Nut	883412			
L	3/8" HF Locknut	3510			
M	Preformed Aluminum Alloy Armor Rods, size req'd				
N	1/8" wire #6 strong alum. alloy				
O	Epoxy Insulator (Extension Link)				
P	35' class 5 creosoted pine pole				
R	Aluminum double tab Squeeze on Connector for ACSR, Aluminum, or Copper-alloy req'd			KEARNEY SERIES "B"	X
S	6" Suspension Insulator	44200			
T	5/8" Standard Oval Eye Nut	6502			
U	Primary Head End Clamp		44050		
W	5/8" x 18" (or length req'd) Double Armring Bolt w/ sq. nut	8868			
X	Buying detail - see dng. No. 85-10 for spec.				
Y	Hot Line Clamp				
Z	Squeeze on basket, size required	5/5204CP		KEARNEY	X

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER			
DESIGN BY:			
CHECKED BY:		PRODUCTION DEPT. (CONOCO)	
APPROVED BY:		HOBBS DIVISION	
SCALE: NONE		JOB: ES-1	
		SHEET 1 OF 1	