

ITEM	DESCRIPTION	A. B. CHANGE NO.	JOSLYN NO.	OTHER VERS. NO.	NO. SUB.
A	35' class 6 creosoted pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	High density wet process porcelain pin insulator		463		
D	5/8" x 5" forged steel pin w/eq. washer, nut, & locknut	081			
E	3/8" x 12" machine bolt w/ nut (or length req'd)	082			
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole sq. washer	083			
G	3/8" HF locknut	352			
H	1/4" x 1 1/4" x 28" flat Crossarm Brace	7128			
J	1/2" x 4" EZ Fetter Drive Log Screw	508754			
K	3/8" x 4 1/2" Carriage Bolt w/ Nut	0834 1/1			
L	3/8" HF locknut	3510			
M	Prefabricated Aluminum Alloy Armor Rods, size req'd				
N	1/4" x 1/2" x 1/2" x 1/2" strong alum. alloy tie wire w/ strong alum. alloy epoxy insulator (extension link)				
O	35' class 5 creosoted pine pole				
P	Aluminum double tab Squeeze on Connector for ACSS, Aluminum, or Copper-size req'd				
R	6" Suspension Insulator	46200			
S	5/8" Standard Oval Eye Nut	4602			
T	Primary Dead End Clamp	44250			
U	5/8" x 18" (or length req'd) Double Arming Bolt w/ 3/4 sq. nuts	0868			
X	Buying detail - see dwg No. HS-10 for specs.				
Y	Hot Line Clamp				
Z	Squeeze on basket, size required	515202GP			

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER			
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE			
PRODUCTION DEPT. CONOCO		HOBBS DIV.	
JOB:		DRAWING NO. ES-1	