

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER NO.	NO. SUB.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	12410/56			X
BB	General Purpose "pin" bolt clamp	12510/60			
CC	Lightening arrester, 10 KV				
DD	Single phase oil switch, 14.4 KV				
EE	split bolt connector, size req'd				
FF	grounding specs. see. dog No. ES-11 & ES-1A, Note 3				
GG	3" class 4, creosoted pine pole				
HH	Aluminum deadend lreforma for ACSR, size req'd				
JJ	30' class 6, creosoted pine pole				
KK	OVERHEAD GRND, #4 ACSR - If Req'd - Ref. Dog ES-11, ES-1A - Note 3				
LL	Ground connector, motor				
MM	600 V. secondary lightning arrester single phase				
NN	Greenfield type EF liquid-tight flexible steel conduit, size req'd, w/ necessary liquid-tight connectors.				
OO	req'd size LB fitting & cover & gasket				
PP	transformer tank grounding terminal				
QQ	Bird Guards (insulating boots on transformer bushings)				

DATE: 12-27-71	TITLE: DESCRIPTION MATERIAL
DRAWN BY: E. WINTER	CONOCO
DESIGN BY:	
CHECKED BY:	
APPROVED BY:	
SCALE: NONE	PRODUCTION DEPT. JOB: REC. SPECS DRAWN BY: E. WINTER SHEET 2 OF 3