DESCRIPTION A. B. CHURE NO. Fold With NO. Fold Wit				•		\vdash	-	qq Ground Connection (See Dwg. ES-12) rr wet process porcelain secondary spo	nn pole bottom ground des(red)		kg medium aize strain i		dd 5/8" x 10" angle th				q 8-way expanding and	+		1 transformer cluster	<pre> transformer cluster }</pre>	h 3/8" x 12" (or 1eng	+	e parallel groove clai	d required size condu size & rated insula Note: provide clam		double upact bolt s cotter key on short on long end, 15 1/8	DE DE
B. CIANCE NO. JOSLYN NO. OTTER NO. SUB.	-						to ascondanty abool (traularor	ē.	place (may use butt-wrapp 11	lift plate	1/8" giv strand	1/2" bolts	imbleye bolt w/nut	for 3/8" guy strand	anenor rod Windt (uma twineye	process porcessin secondary	hor (size reg'd)	ES-18	t diaroonant & fuara 3-ohaar	mount bracket (large)	transformer cluster mount bracket (small)	length req'd) straight thimbleye	clevis for 4" insulator	mp, size req'd	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. Dwg ES-18 Note: provide clamp and ground conduit	in secondary spool insulator,	/sq, nut, round washer, and end, sq. nut and HF locknut "long (or length required.)	DESCRIPTION
N NO. OTTER NO. NO. HTRS. NO. SUB.										7887	6454		5010 6813 Vz		5317 (HUT 55006P)		88135	X-16				55/2	6510				7828	
SUB.	 1	 						, ,	• ***							10105	A			4.8¥ 6 .			A d b n			101		JOSLYN NO.
SUB.		 																		ALUMA FORM ISM3-6	ALUMA-FORM 6M 3-6			BURNDY SERIES UC				OTHER MFRS, NO.
		APPROVED BY:	CHECKED BY:	DESIGN BY	DRAWN BY			- - - -	•	×			×					:		×	×				<u> </u>			NO.

Q