

LIST TYPE OF STRING BY CODE LETTERS, i.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINER (L); PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)

FROM-TO	OD	DRAFT ID	WT PER FT	GRADE	THREAD	AMT	WT. IN AIR, WT. IN MUD		REMARKS
							1000 LBS	1000 LBS	
(S) 0'-1350'	8 5/8"	7.972"	24.00	K-55	STC	1350'			Sand blast bottom 5'
(P) 0'-3800'	5 1/2"	4.825"	15.50	K-55	STC	3800'			

TYPE OF STRING	CENTRALIZERS		SCRATCHER		OTHER ACCESSORY EQUIPMENT		REMARKS
	INTERVAL		NO. INTERVAL		(SUCH AS DEGASSERS, MUD, CENTRIFUGE		
	NO. FROM-TO	NO. FROM-TO	NO. FROM-TO	NO. FROM-TO	FLOAT COLLARS, ETC. - SPECIFY)		
(S) Surface	100' spacing (13) 0'-1350'	15' spacing None			Guide shoe & float collar		
(P) Production	(2) 1200'-1300' (53) 3000-3800' Float shoe & float collar (above 8 5/8" (over pay zones) shoe)						
	(20) 3000'-3800'						
	(1 every joint over pay zone)						