

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Summit Energy, Inc.	8. Farm or Lease Name Amanda Sims
3. Address of Operator 112 N. First St., Artesia, New Mexico 88210	9. Well No. 2
4. Location of Well UNIT LETTER <u>I</u> , <u>990</u> FEET FROM THE <u>East</u> LINE AND <u>2310'</u> FEET FROM THE <u>South</u> LINE, SECTION <u>25</u> TOWNSHIP <u>22 S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat Wantz Granite Wash
15. Elevation (Show whether DF, RT, GR, etc.) 3308.0 GR.	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 1177'. Ran 28 joints 8 5/8" - 24# - K55 Casing. Cemented with 200 sacks Class C lite poz with 6% gel and 2% CaCl, plus 200 sacks Class C cement with 2% CaCl, no gel. Cement circulated. Plug down @ 10:30 p.m. 3-26-80. After 24 hours, tested 8 5/8" casing to 2000 psi for 30 minutes. Tested okay. Drilled out 8 5/8" cement plug and tested for 1 hour to 2000 psi. Tested okay.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Pavel White</u>	TITLE <u>Engineer</u>	DATE <u>3-28-80</u>
APPROVED BY <u>Orig. Signed by Jerry Sexton</u>	TITLE <u>Dist. 1. Supv.</u>	DATE <u>3-28-80</u>
CONDITIONS OF APPROVAL		