

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

5a. Indicate Type of Lease

State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Summit Energy, Inc.	8. Farm or Lease Name Amanda Sims
3. Address of Operator 112 North 1st., Artesia, New Mexico 88210	9. Well No. 2
4. Location of Well UNIT LETTER <u>I</u> , <u>990</u> FEET FROM THE <u>East</u> LINE AND <u>2310</u> FEET FROM THE <u>South</u> LINE, SECTION <u>25</u> TOWNSHIP <u>22 S</u> RANGE <u>37 East</u> NMPM.	10. Field and Pool, or Wildcat Drinkard Oil
15. Elevation (Show whether DF, RT, GR, etc.) 3308.0 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7 7/8" hole to 7550'. Ran logs. Ran 233 jts. of 5 1/2" 17# casing. Set casing at 7549'. Ran (1) Cement stage collar below base of salt at 2891'. Cemented 1st stage with 500 sx Class C 65-35 Pozmix followed by 250 sx Class C Pozmix with 3#/salt per sack. First stage completed at 2:30 p.m. (4-17-80) Cemented 2nd stage throw stage collar at 2891' with 850 sx. Class C 65-35 Pozmix followed by 200 sx Class C with 18% Dowell 44 additive. 2nd stage completed at 1:00 a.m. (4-18-80). On May 13, 1980, moved in reverse unit and pump. Tested casing to 3000 psi for 1 hour. Tested o.k.. Drilled out stage collar. Tested casing to 3000 psi for 1 hour. Tested o.k.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Frank D. White

TITLE Engineer

DATE 5-27-80

APPROVED BY Orig. Signed By Jerry Sexton

TITLE

DATE MAY 29 1980

CONDITIONS OF APPROVAL, IF ANY: