

UNIT STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved,
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM - 15035

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

7. UNIT AGREEMENT NAME

Antelope Ridge

8. FARM OR LEASE NAME

Supron Fed Comm

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Morrow & Antelope Ridge Atoka

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 14-23S-34E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

NATOMAS NORTH AMERICA, INC.

3. ADDRESS OF OPERATOR

1000 First Place, Tulsa, Oklahoma 74103

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

1980' FWL & 1980' FSL, Sec. 14-23S-34E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing Test & Cement Job

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

5-17-80 Run 18 jts., 750' - 20" 94# H-40 STC Casing Cemented w/925 sx Class "C", Tailed
in w/400 sx Class C w/good Returns WOC 24 hrs.

6-07-80 Run 116 jts. 5044' 13-3/8" csg - 22 jts 72# S-80 94 jts 68# S-80. DV tool @
1500'. Cemented w/2450 sx HLC Tailed in 350 sx Class "C" no return, first
stage. Cemented w/1200 sx Class H and 200 sx HLC Class C. Good returns,
second stage. WOC 24 hrs. Tested Casing to 1500 psi.

RECEIVED

JUL 8 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Steve Green

TITLE Area Engineer

DATE 7/2/80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
DATE

*See Instructions on Reverse Side

JUL 7 1980
K.E. Sayles
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

RECEIVED
JUL 15 1980
OIL CONSERVATION DIV.