

DISTRIBUTION		
DATE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Supersedes Old
C-100 and C-103
Effective 1-1-65

1a. Indicate Type of Lease
State ☐ Fee ☒
1b. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☒ GAS WELL ☐ OTHER ☐
Name of Operator
SHELL OIL COMPANY
Address of Operator
P. O. BOX 991, HOUSTON, TX 77001
Location of Well
UNIT LETTER I 1940 FEET FROM THE South LINE AND 380 FEET FROM
THE East LINE, SECTION 8 TOWNSHIP 22S RANGE 37E N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
Grizzell
9. Well No.
10
10. Field and Pool, or Wildcat
Brunson/Fusselman
11. County
Lea

15. Elevation (Show whether DF, RT, GR, etc.)
3405.7 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 4-18-80: Drilled out DV Tool & tagged TOC @7380'.
- 4-19-80: Drilled out cmt. to 7461' & tested csg to 2000 psi. Held OK. Ran GR/CCL from 7461' to 3900'. Perf'd 5 1/2" csg w/3 way gun @ 6165'. Press'd to 2000 psi. No circulation. Ran pkr to 6180' & spotted 200 gals 15% NEA from 6180'-5980'. Reset pkr @5850'. Ppd 1000 gals 15% NEA. Lowered pkr to 6200'.
- 4-20-80: Set cmt retainer @6075'. Ppd 100 sx Class C cmt w/5# salt/sx. Ran temperature bomb & found TOC @5950'.
- 4-21-80: Drilled cmt retainer, lowered bit to 7461' & circulated hole. Press'd csg to 2000 psi. 20 min bled back to 1400 psi. Pld 100 jts tbg.
- 4-22-80: Ran cmt bond log. TOC @5982'.
- 4-23-80: Spotted 2 sx sand on top of BP. Pld 2" tbg. Perf'd 5 1/2" csg w/3 way jet shot @5350'. Set 2" retainer on 2" tbg & set @5250'. Ppd thru perforations & circulated out bradenhead. Ppd 700 sx Class C cmt, last 100 sx containing 5# salt/sx. Ran temperature log. TOC @1730'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed A. J. Fore A. J. FORE TITLE SR. ENGR. TECH. DATE 4-30-80

APPROVED BY Jerry Sexton TITLE Dist. 1. Supv. DATE MAY 1 1980
CONDITIONS OF APPROVAL, IF ANY: