- Submit 3 Copies to Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources Depar	Timent Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 <u>DISTRICT II</u> P.O. Drawer DD, Artesia, NM 88210	OIL CONSERVATION DIVIS P.O. Box 2088 Santa Fe, New Mexico 87504-2088	WELL API NO.           30-025-26766           5. Indicate Type of Lease           STATE X   FEE
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 8741	0	6. State Oil & Gas Lease No. V-3959
( DO NOT USE THIS FORM FOR I	DTICES AND REPORTS ON WELLS PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BAC SERVOIR. USE "APPLICATION FOR PERMIT" A C-101) FOR SUCH PROPOSALS.)	K TO A 7. Lease Name or Unit Agreement Name
1. Type of Well: OB. GAS WELL X WELL	OTHER	Quay AQU State
2. Name of Operator		8. Well No.
YATES PETROLEUM CORP	ORATION	9. Pool name or Wildcat
3. Address of Operator 105 South 4th St., A	rtesia, NM 88210	Und. North Bell Lake Wolfcamp
4. Well Location Unit LetterC :6 Section 10	D60       Feet From The       North       Line and         Township       23S       Range       33E         10. Elevation (Show whether DF, RKB, RT, G         3590.6'       GR	NMPM Lea County
11. Che	ck Appropriate Box to Indicate Nature of N	otice, Report, or Other Data
NOTICE OF	INTENTION TO:	SUBSEQUENT REPORT OF:
PULL OR ALTER CASING	CASING TE	
DTHER:		Re-entry X
work) SEE RULE 1103. 1-29-97 - Clenaed 1 slips on 7-5/8" cas spool. Tested pack 1-30-97 - Nippled u bottom hole collar. of 6-13/16" ID. Ni 1-31-97 - Nippled d 3000#. Nippled up Tagged top plug at Installed stripper 11 joints of tubing ot 725' Drilled (	<pre>ing with 60K. Cut off and instal ing to 3000#. p BOP. Tested blind rams to 1500 Bit wouldnot pass through tubin ppled down BOP. Wait on new tubi lown 6-3/8" ID spool and nippled u BOP. Test blind rams to 1500#. 57'. Laid down 1 drill collar an and rigged up swivel. Drilled ha POOW and picked up 9 4-3/4" dr</pre>	n and rigged up pulling unit. Set led 11" 3000 X 7-1/16" 5000 tubing #. Picked up 6-1/2" skirted bit on g spool. Spool has 6-3/8" ID instead nghead. p 6-13/16" spool. Tested seals to Picked up 6-1/2" bit and drill collars d picked up 1 joint of tubing. rd cement from 57' to 65'. TIH with ill collars. TIH and tagged plug #2 lean. Shut down for night. NOTE:
I hereby certify that the information abov	e is true and complete to the best of my knowledge and belief.	tions Technician Jan. 31, 1997
SKONATURE TUSLy Rusty K		тецерноле но. 505/748-1
TIPEORPERITING	این که با این میشند. بیشن با این می با این این میشن این میشن با مشاور مشاور با ماند. این می با این می مشاور ای این می با این می با این می با این می این می والد و می از می والد می با این می با این می والد می والد می والد می	
(This space for State UsePRIGINAL DIS	SIGNED RY IERAN	
DIS	TRICE I SUPERVISOR	DATE 53 55 1197