

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
24146	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
Name of Operator		8. Farm or Lease Name
GULF OIL CORPORATION		R. E. Cole (NCT-A)
Address of Operator		9. Well No.
P. O. Box 670, Hobbs, NM 88240		22
Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER A - 890 FEET FROM THE North LINE AND 990 FEET FROM East LINE, SECTION 16 TOWNSHIP 22S RANGE 37E N.M.P.M.		Brunson Ellenburger
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3402' GL		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7940' TD 6230' PB Ran 166 joints & 1 cut joint 5½" 14# K-55 ST&C (2104' Class "B", 4109' Class "A") 6213' set at 6230' with float collar at 6203'. Halco cement with 1000 sacks Class "C" with 16% gel Gulfmix & 450 sacks "C" neat. Plug down at 2:45 AM, 6-25-80. Circulate. Wait on cement 18 hours. Pressure tested casing to 3500#, ok.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. L. Venable TITLE Area Drilling Supt. DATE JUL 10 1980

APPROVED BY Jerry Sexton TITLE Supv. DATE JUL 10 1980
CONDITIONS OF APPROVAL See 1103