

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
24146	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
GULF OIL CORPORATION		R. E. Cole (NCT-A)
3. Address of Operator		9. Well No.
P. O. Box 670, Hobbs, New Mexico 88240		22
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>A</u> <u>890</u> FEET FROM THE <u>North</u> LINE AND <u>990</u> FEET FROM		Brunson Ellenburger
THE <u>East</u> LINE, SECTION <u>16</u> TOWNSHIP <u>22S</u> RANGE <u>37E</u> N.M.P.M.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3402' GL		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPER. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ard Drilling Company spudded 14-3/4" surface hole at 11 PM, 5-29-80; drilled to 335'.  
Ran 7 joints and 1 cut joint 11-3/4" 42# H-40 ST&C (318') set at 335' with insert float  
at 297'. Cemented by BJ with 250 sacks Class "C" 2% CaCl<sub>2</sub>. Plug down at 5 PM, 5-30-80.  
Circulated 15 sacks. WOC 18 hours. Tested BOP and casing 1000#. Drill plug, float and  
cement.

Started drilling 11" hole at 2:30 PM, 5-31-80.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. R. Knight TITLE Area Drilling Supt. DATE 6-3-80

APPROVED BY Jerry Sexton TITLE  DATE 1980

CONDITIONS OF APPROVAL